








- | | |
|---|---|
|  | KEY
Site boundary |
|  | Existing trees and vegetation to be retained |
|  | Existing trees and vegetation to be removed |
|  | Soft Landscape Proposals
Refer to plant schedule for details. |
|  | 12m high Timber post and rail fencing
1.2m high mortised 3 bar post and rail fence to attenuation basin, as supplied by Jackson Fencing or similar approved. |
|  | Tree root barrier locations
Location of tree root protection barriers. Relroot 600 GreenVue Urban Ltd (or similar approved) to be specified to protect path grade and deflect root growth downwards. Relroot 600 GreenVue Urban Ltd (or similar approved). 1000mm depth to be specified to the edge of the verge and extended minimum of 2m beyond the expected mature tree canopy, or within 2m of services (to be installed on the side of services only) as directed by the project engineers. |
|  | Compacted gravel/hoggin footpath
200mm wide 50mm rigid hoggin surface on 100mm type 1 sub base. To be timber edged and cambered on both sides to shed surface water. Tires are essential to ensure the surface compacts. Self binding gravel layer to be well compacted with vibratory roller. |
|  | Bench seating
Ref: BMT 47021 Rooin Bench" steel framed timber seating system, as supplied by Broxap or similar approved. Bench to be installed with underlaid fixing set in concrete footings to manufacturers specification. |
|  | Litter bin
Galvanised steel litter bin, 145L capacity, polyester powder coating, colour: RAL 9005 Jet Black, bolt down using to concrete foundation. Ref: BAK55 2550-E-145 Benly® F.L. Litter Bin, as supplied by Broxap or similar approved. |
|  | Dog waste bin
Galvanised steel body, polyester powder coated, colour: RAL 9005 Green, bolt down using to concrete foundation. Ref: AKS5 2591-P-145 AKS 400L, cast mounted dog waste bin, as supplied by Broxap or similar approved. |

A	06.06.26	Co-ordination with airb survey.	AP	AP
=	13.04.26	First issue	OG	AP