



MATERIALS PALLETTE:

PAVESTONE ABBEY LIMESTONE OR SIMILAR
APPROVED RIVEN PAVING SLABS



PAVESTONE SLIMSETT OR SIMILAR APPROVED
BLOCK PAVING



ECOGRID E50 OR SIMILAR
CELLULAR RETAINMENT SYSTEM
TO PARKING, ROADWAY AND PATHS



2M BATTENED FENCE AND MATCHING GATE TO HOT-TUB AREA



Everedge or similar steel edging to paths and borders

Slab Paving

To be chosen by client with samples to be provided and approved.
Falls to be always away from buildings and towards drains or run-offs and sufficient so that no water shall stand.
Laying method to be as per manufacturers recommendations. Block/Beam or Compacted Hardcore as appropriate.
All paved areas to be haunched/shored at any free edges to half the depth of the slab at an angle of 45 degrees.
Paving layout dimensions are approximate, always finish paving edge on a full slab/block where possible.

Block Paving

To be chosen by client with samples to be provided and approved.
Falls to be always away from buildings and towards drains or run-offs and sufficient so that no water shall stand.
Laying method to be as per manufacturers recommendations.
All paved areas to be haunched/shored at any free edges to half the depth of the slab at an angle of 45 degrees.
Paving layout dimensions are approximate, always finish paving edge on a full slab/block where possible.

Steps

To be 150mm high and of consistent height.
Tread slab to have 20-25mm overhang.
Face/riser to be slab/tile to match.

Gravel

Use an angular (not rounded pebbles) 10-15mm pale decorative aggregate (not limestone/cotswold buff). Use Ecogrid, Golpla or similar gravel retention system to driveway, colour of units should match aggregate as closely as possible.
Use Landscape membrane under all gravel areas.
Samples to be provided and agreed with client.

Inspection Covers

All new inspection covers are to be tray style recessed covers with the paving pattern carried through exactly. In the event that an inspection cover clashes with a wall or other feature, please refer to Alan Capeling for revision.

Walling

All visible walling to upper terrace to be faced with brick to match house.
Copings to match pale paving slab.
Line rear of walls with Black DPM and include weep holes and expansion/movement joints as necessary.

General

All works to be carried out by or under the direct supervision of an experienced and qualified landscaper. The scheme should be entirely laid out and adjustments made as necessary prior to hard landscaping works begining.
All designs for retaining and other load bearing structures should be checked and verified by a structural engineer.
With any excavations there is a chance of finding major services, please make sure the necessary steps are taken to avoid injury and disruption to services.
No elements of the design should be dangerous to build or maintain, if there are any concerns over health and safety please contact CLD Ltdso that the design can be revised.

If any information is missing, incorrect or unclear please contact CLD Ltd.
For quotation purposes and during construction all dimensions must be checked on site by the contractor.
Please contact CLD Ltd if you have any questions during quoting or construction.
Further drawings and details are available on request.

Project: Elmsdale House, Sheepy Magna

Drawing: Layout 1 of 4

Scale: 1:200 @ A1 (All dimensions must be checked on site)

Version: D

Date: 14/06/23

Drawn by: AJC

22 Gladstone Street
Loughborough
Leicestershire
LE11 1DNS
design@alancapeling.co.uk

0777 5758949
01509 567183

www.alancapeling.co.uk

 **CAPELING**
LANDSCAPE DESIGN LTD