

Design Settings

Rainfall Methodology	FSR	Maximum Time of Concentration (mins)	30.00
Return Period (years)	2	Maximum Rainfall (mm/hr)	0.0
Additional Flow (%)	0	Minimum Velocity (m/s)	1.00
FSR Region	England and Wales	Connection Type	Level Soffits
M5-60 (mm)	20.000	Minimum Backdrop Height (m)	9.900
Ratio-R	0.400	Preferred Cover Depth (m)	1.500
CV	0.750	Include Intermediate Ground	✓
Time of Entry (mins)	5.00	Enforce best practice design rules	✓

Nodes

Name	Area (ha)	T of E (mins)	Cover Level (m)	Diameter (mm)	Easting (m)	Northing (m)	Depth (m)
61	0.116	5.00	127.139	1200	444768.510	303022.475	1.725
72	0.081	5.00	128.287	1200	444825.434	302985.788	1.725
73	0.022	5.00	127.818	1500	444825.439	303012.844	1.668
76	0.027	5.00	128.843	1200	444884.227	303033.307	1.631
78	0.047	5.00	128.511	1500	444863.690	303039.713	1.790
74	0.083	5.00	127.962	1200	444828.168	303040.018	2.389
75	0.086	5.00	127.725	1200	444813.183	303042.079	2.407
62	0.097	5.00	127.322	1500	444779.278	303050.999	2.669
63	0.022	5.00	127.210	1500	444787.030	303073.936	2.710
64	0.035	5.00	126.870	1500	444791.627	303099.555	2.570
65	0.058	5.00	126.583	1500	444770.906	303104.466	2.433
66	0.095	5.00	125.900	1500	444743.092	303115.175	1.900
67	0.215	5.00	125.550	1500	444758.031	303155.770	1.650
68			125.200	1500	444772.154	303179.379	1.450
79	0.105	5.00	127.978	1200	444905.219	303094.375	1.725
80	0.091	5.00	127.787	1200	444875.201	303096.724	2.040
88	0.123	5.00	127.168	1200	444818.922	303097.398	1.725
81	0.066	5.00	127.317	1200	444832.830	303097.561	2.208
82	0.065	5.00	125.904	1500	444833.047	303151.357	1.454
83	0.146	5.00	126.600	1200	444874.793	303151.284	2.375
84			125.600	1500	444873.877	303164.741	1.420
85			125.600	1500	444851.001	303168.407	1.500
86			125.400	1500	444833.873	303169.060	1.400
87			125.200	1500	444815.843	303170.781	1.350
69			125.200	1500	444769.580	303181.271	1.500
70			125.200	1500	444764.191	303187.829	1.550
71			124.300	1500	444765.358	303196.429	0.700

Links

Name	US Node	DS Node	Length (m)	ks (mm) / n	US IL (m)	DS IL (m)	Fall (m)	Slope (1:X)	Dia (mm)	T of C (mins)	Rain (mm/hr)
1.000	61	62	30.489	0.600	125.414	124.803	0.611	49.9	300	5.23	0.0
2.000	72	73	27.056	0.600	126.562	126.300	0.262	103.3	225	5.35	0.0
2.001	73	74	27.311	0.600	126.150	125.573	0.577	47.3	375	5.52	0.0
3.000	76	78	21.513	0.600	127.212	126.796	0.416	51.7	225	5.20	0.0
3.002	78	74	35.523	0.600	126.721	125.648	1.073	33.1	300	5.41	0.0
2.002	74	75	15.126	0.600	125.573	125.318	0.255	59.3	375	5.63	0.0
2.003	75	62	35.059	0.600	125.318	124.728	0.590	59.4	375	5.88	0.0
1.001	62	63	24.212	0.600	124.653	124.500	0.153	158.2	450	6.13	0.0
1.002	63	64	26.028	0.600	124.500	124.300	0.200	130.1	450	6.37	0.0
1.003	64	65	21.295	0.600	124.300	124.150	0.150	142.0	450	6.58	0.0
1.004	65	66	29.804	0.600	124.150	124.000	0.150	198.7	450	6.93	0.0
1.005	66	67	43.257	0.600	124.000	123.900	0.100	432.6	450	7.67	0.0
1.006	67	68	27.511	0.600	123.900	123.750	0.150	183.4	450	7.97	0.0
1.007	68	69	3.195	0.600	123.750	123.700	0.050	63.9	525	7.99	0.0
4.000	79	80	30.110	0.600	126.253	125.747	0.506	59.5	225	5.30	0.0
4.001	80	81	42.379	0.600	125.747	125.109	0.638	66.4	225	5.74	0.0
5.000	88	81	13.909	0.600	125.443	125.109	0.334	41.6	225	5.11	0.0
4.002	81	82	53.796	0.600	125.109	124.600	0.509	105.7	300	6.32	0.0
4.003	82	83	41.746	0.600	124.450	124.300	0.150	278.3	450	6.90	0.0
4.004	83	84	13.488	0.600	124.225	124.180	0.045	299.7	525	7.07	0.0
4.005	84	85	23.168	0.600	124.180	124.100	0.080	289.6	600	7.34	0.0
4.006	85	86	17.140	0.600	124.100	124.000	0.100	171.4	525	7.51	0.0
4.007	86	87	18.112	0.600	124.000	123.850	0.150	120.7	525	7.66	0.0
4.008	87	69	47.437	0.600	123.850	123.700	0.150	316.2	525	8.29	0.0

Name	Vel (m/s)	Cap (l/s)	Flow (l/s)	US Depth (m)	DS Depth (m)	Σ Area (ha)	Σ Add Inflow (l/s)	Pro Depth (mm)	Pro Velocity (m/s)
1.000	2.231	157.7	0.0	1.425	2.219	0.116	0.0	0	0.000
2.000	1.286	51.1	0.0	1.500	1.293	0.081	0.0	0	0.000
2.001	2.639	291.5	0.0	1.293	2.014	0.103	0.0	0	0.000
3.000	1.823	72.5	0.0	1.406	1.490	0.027	0.0	0	0.000
3.002	2.741	193.8	0.0	1.490	2.014	0.074	0.0	0	0.000
2.002	2.356	260.2	0.0	2.014	2.032	0.260	0.0	0	0.000
2.003	2.354	260.0	0.0	2.032	2.219	0.346	0.0	0	0.000
1.001	1.613	256.6	0.0	2.219	2.260	0.559	0.0	0	0.000
1.002	1.780	283.1	0.0	2.260	2.120	0.581	0.0	0	0.000
1.003	1.704	271.0	0.0	2.120	1.983	0.616	0.0	0	0.000
1.004	1.438	228.8	0.0	1.983	1.450	0.674	0.0	0	0.000
1.005	0.971	154.4	0.0	1.450	1.200	0.769	0.0	0	0.000
1.006	1.498	238.2	0.0	1.200	1.000	0.984	0.0	0	0.000
1.007	2.805	607.2	0.0	0.925	0.975	0.984	0.0	0	0.000
4.000	1.698	67.5	0.0	1.500	1.815	0.105	0.0	0	0.000
4.001	1.607	63.9	0.0	1.815	1.983	0.196	0.0	0	0.000
5.000	2.033	80.8	0.0	1.500	1.983	0.123	0.0	0	0.000
4.002	1.529	108.1	0.0	1.908	1.004	0.385	0.0	0	0.000
4.003	1.213	193.0	0.0	1.004	1.850	0.450	0.0	0	0.000
4.004	1.288	278.9	0.0	1.850	0.895	0.596	0.0	0	0.000
4.005	1.426	403.1	0.0	0.820	0.900	0.596	0.0	0	0.000
4.006	1.708	369.7	0.0	0.975	0.875	0.596	0.0	0	0.000
4.007	2.037	441.0	0.0	0.875	0.825	0.596	0.0	0	0.000
4.008	1.254	271.4	0.0	0.825	0.975	0.596	0.0	0	0.000

Links

Name	US Node	DS Node	Length (m)	ks (mm) / n	US IL (m)	DS IL (m)	Fall (m)	Slope (1:X)	Dia (mm)	T of C (mins)	Rain (mm/hr)
1.008	69	70	8.488	0.600	123.700	123.650	0.050	169.8	525	8.37	0.0
1.009	70	71	8.679	0.600	123.650	123.600	0.050	173.6	450	8.46	0.0

Name	Vel (m/s)	Cap (l/s)	Flow (l/s)	US Depth (m)	DS Depth (m)	Σ Area (ha)	Σ Add Inflow (l/s)	Pro Depth (mm)	Pro Velocity (m/s)
1.008	1.716	371.5	0.0	0.975	1.025	1.580	0.0	0	0.000
1.009	1.540	244.9	0.0	1.100	0.250	1.580	0.0	0	0.000

Pipeline Schedule

Link	Length (m)	Slope (1:X)	Dia (mm)	Link Type	US CL (m)	US IL (m)	US Depth (m)	DS CL (m)	DS IL (m)	DS Depth (m)
1.000	30.489	49.9	300	Circular_Default Sewer Type	127.139	125.414	1.425	127.322	124.803	2.219
2.000	27.056	103.3	225	Circular_Default Sewer Type	128.287	126.562	1.500	127.818	126.300	1.293
2.001	27.311	47.3	375	Circular_Default Sewer Type	127.818	126.150	1.293	127.962	125.573	2.014
3.000	21.513	51.7	225	Circular_Default Sewer Type	128.843	127.212	1.406	128.511	126.796	1.490
3.002	35.523	33.1	300	Circular_Default Sewer Type	128.511	126.721	1.490	127.962	125.648	2.014
2.002	15.126	59.3	375	Circular_Default Sewer Type	127.962	125.573	2.014	127.725	125.318	2.032
2.003	35.059	59.4	375	Circular_Default Sewer Type	127.725	125.318	2.032	127.322	124.728	2.219
1.001	24.212	158.2	450	Circular_Default Sewer Type	127.322	124.653	2.219	127.210	124.500	2.260
1.002	26.028	130.1	450	Circular_Default Sewer Type	127.210	124.500	2.260	126.870	124.300	2.120
1.003	21.295	142.0	450	Circular_Default Sewer Type	126.870	124.300	2.120	126.583	124.150	1.983
1.004	29.804	198.7	450	Circular_Default Sewer Type	126.583	124.150	1.983	125.900	124.000	1.450
1.005	43.257	432.6	450	Circular_Default Sewer Type	125.900	124.000	1.450	125.550	123.900	1.200
1.006	27.511	183.4	450	Circular_Default Sewer Type	125.550	123.900	1.200	125.200	123.750	1.000
1.007	3.195	63.9	525	Circular_Default Sewer Type	125.200	123.750	0.925	125.200	123.700	0.975
4.000	30.110	59.5	225	Circular_Default Sewer Type	127.978	126.253	1.500	127.787	125.747	1.815
4.001	42.379	66.4	225	Circular_Default Sewer Type	127.787	125.747	1.815	127.317	125.109	1.983
5.000	13.909	41.6	225	Circular_Default Sewer Type	127.168	125.443	1.500	127.317	125.109	1.983
4.002	53.796	105.7	300	Circular_Default Sewer Type	127.317	125.109	1.908	125.904	124.600	1.004



Link	US Node	Dia (mm)	Node Type	MH Type	DS Node	Dia (mm)	Node Type	MH Type
1.000	61	1200	Manhole	Adoptable	62	1500	Manhole	Adoptable
2.000	72	1200	Manhole	Adoptable	73	1500	Manhole	Adoptable
2.001	73	1500	Manhole	Adoptable	74	1200	Manhole	Adoptable
3.000	76	1200	Manhole	Adoptable	78	1500	Manhole	Adoptable
3.002	78	1500	Manhole	Adoptable	74	1200	Manhole	Adoptable
2.002	74	1200	Manhole	Adoptable	75	1200	Manhole	Adoptable
2.003	75	1200	Manhole	Adoptable	62	1500	Manhole	Adoptable
1.001	62	1500	Manhole	Adoptable	63	1500	Manhole	Adoptable
1.002	63	1500	Manhole	Adoptable	64	1500	Manhole	Adoptable
1.003	64	1500	Manhole	Adoptable	65	1500	Manhole	Adoptable
1.004	65	1500	Manhole	Adoptable	66	1500	Manhole	Adoptable
1.005	66	1500	Manhole	Adoptable	67	1500	Manhole	Adoptable
1.006	67	1500	Manhole	Adoptable	68	1500	Manhole	Adoptable
1.007	68	1500	Manhole	Adoptable	69	1500	Manhole	Adoptable
4.000	79	1200	Manhole	Adoptable	80	1200	Manhole	Adoptable
4.001	80	1200	Manhole	Adoptable	81	1200	Manhole	Adoptable
5.000	88	1200	Manhole	Adoptable	81	1200	Manhole	Adoptable
4.002	81	1200	Manhole	Adoptable	82	1500	Manhole	Adoptable

Pipeline Schedule






Link	Length (m)	Slope (1:X)	Dia (mm)	Link Type	US CL (m)	US IL (m)	US Depth (m)	DS CL (m)	DS IL (m)	DS Depth (m)
4.003	41.746	278.3	450	Circular_Default Sewer Type	125.904	124.450	1.004	126.600	124.300	1.850
4.004	13.488	299.7	525	Circular_Default Sewer Type	126.600	124.225	1.850	125.600	124.180	0.895
4.005	23.168	289.6	600	Circular_Default Sewer Type	125.600	124.180	0.820	125.600	124.100	0.900
4.006	17.140	171.4	525	Circular_Default Sewer Type	125.600	124.100	0.975	125.400	124.000	0.875
4.007	18.112	120.7	525	Circular_Default Sewer Type	125.400	124.000	0.875	125.200	123.850	0.825
4.008	47.437	316.2	525	Circular_Default Sewer Type	125.200	123.850	0.825	125.200	123.700	0.975
1.008	8.488	169.8	525	Circular_Default Sewer Type	125.200	123.700	0.975	125.200	123.650	1.025
1.009	8.679	173.6	450	Circular_Default Sewer Type	125.200	123.650	1.100	124.300	123.600	0.250

Link	US Node	Dia (mm)	Node Type	MH Type	DS Node	Dia (mm)	Node Type	MH Type
4.003	82	1500	Manhole	Adoptable	83	1200	Manhole	Adoptable
4.004	83	1200	Manhole	Adoptable	84	1500	Manhole	Adoptable
4.005	84	1500	Manhole	Adoptable	85	1500	Manhole	Adoptable
4.006	85	1500	Manhole	Adoptable	86	1500	Manhole	Adoptable
4.007	86	1500	Manhole	Adoptable	87	1500	Manhole	Adoptable
4.008	87	1500	Manhole	Adoptable	69	1500	Manhole	Adoptable
1.008	69	1500	Manhole	Adoptable	70	1500	Manhole	Adoptable
1.009	70	1500	Manhole	Adoptable	71	1500	Manhole	Adoptable




Manhole Schedule

Node	Easting (m)	Northing (m)	CL (m)	Depth (m)	Dia (mm)	Connections	Link	IL (m)	Dia (mm)
61	444768.510	303022.475	127.139	1.725	1200				
						0	1.000	125.414	300
72	444825.434	302985.788	128.287	1.725	1200				
						0	2.000	126.562	225
73	444825.439	303012.844	127.818	1.668	1500				
						0	2.001	126.150	375
76	444884.227	303033.307	128.843	1.631	1200				
						0	3.000	127.212	225
78	444863.690	303039.713	128.511	1.790	1500				
						0	3.002	126.721	300
74	444828.168	303040.018	127.962	2.389	1200				
						2	2.001	125.573	375
						0	2.002	125.573	375
75	444813.183	303042.079	127.725	2.407	1200				
						1	2.002	125.318	375
						0	2.003	125.318	375

Manhole Schedule

Node	Easting (m)	Northing (m)	CL (m)	Depth (m)	Dia (mm)	Connections	Link	IL (m)	Dia (mm)	
62	444779.278	303050.999	127.322	2.669	1500		1	2.003	124.728	375
						2	1.000	124.803	300	
						0	1.001	124.653	450	
63	444787.030	303073.936	127.210	2.710	1500		1	1.001	124.500	450
						0	1.002	124.500	450	
64	444791.627	303099.555	126.870	2.570	1500		1	1.002	124.300	450
						0	1.003	124.300	450	
65	444770.906	303104.466	126.583	2.433	1500		1	1.003	124.150	450
						0	1.004	124.150	450	
66	444743.092	303115.175	125.900	1.900	1500		1	1.004	124.000	450
						0	1.005	124.000	450	
67	444758.031	303155.770	125.550	1.650	1500		1	1.005	123.900	450
						0	1.006	123.900	450	
68	444772.154	303179.379	125.200	1.450	1500		1	1.006	123.750	450
						0	1.007	123.750	525	
79	444905.219	303094.375	127.978	1.725	1200		0	4.000	126.253	225
80	444875.201	303096.724	127.787	2.040	1200		1	4.000	125.747	225
						0	4.001	125.747	225	
88	444818.922	303097.398	127.168	1.725	1200		0	5.000	125.443	225
81	444832.830	303097.561	127.317	2.208	1200		1	5.000	125.109	225
						2	4.001	125.109	225	
						0	4.002	125.109	300	
82	444833.047	303151.357	125.904	1.454	1500		1	4.002	124.600	300
						0	4.003	124.450	450	
83	444874.793	303151.284	126.600	2.375	1200		1	4.003	124.300	450
						0	4.004	124.225	525	

Manhole Schedule

Node	Easting (m)	Northing (m)	CL (m)	Depth (m)	Dia (mm)	Connections	Link	IL (m)	Dia (mm)	
84	444873.877	303164.741	125.600	1.420	1500		1	4.004	124.180	525
85	444851.001	303168.407	125.600	1.500	1500		0	4.005	124.180	600
						1	4.005	124.100	600	
86	444833.873	303169.060	125.400	1.400	1500		0	4.006	124.100	525
						1	4.006	124.000	525	
87	444815.843	303170.781	125.200	1.350	1500		0	4.007	124.000	525
						1	4.007	123.850	525	
69	444769.580	303181.271	125.200	1.500	1500		1	4.008	123.700	525
						2	1.007	123.700	525	
						0	1.008	123.700	525	
70	444764.191	303187.829	125.200	1.550	1500		1	1.008	123.650	525
						0	1.009	123.650	450	
71	444765.358	303196.429	124.300	0.700	1500		1	1.009	123.600	450

Simulation Settings

Rainfall Methodology	FSR	Analysis Speed	Normal
Rainfall Events	Singular	Skip Steady State	✓
FSR Region	England and Wales	Drain Down Time (mins)	240
M5-60 (mm)	20.000	Additional Storage (m³/ha)	20.0
Ratio-R	0.400	Starting Level (m)	
Summer CV	0.750	Check Discharge Rate(s)	x
Winter CV	0.840	Check Discharge Volume	x

Storm Durations

15 | 30 | 60 | 120 | 180 | 240 | 360 | 480 | 600 | 720 | 960 | 1440

Return Period (years)	Climate Change (CC %)	Additional Area (A %)	Additional Flow (Q %)
2	0	0	0
30	0	0	0
100	40	0	0

Node 70 Online Hydro-Brake® Control

Flap Valve	x	Objective	(HE) Minimise upstream storage
Replaces Downstream Link	✓	Sump Available	✓
Invert Level (m)	123.650	Product Number	CTL-SHE-0152-1100-1000-1100
Design Depth (m)	1.000	Min Outlet Diameter (m)	0.225
Design Flow (l/s)	11.0	Min Node Diameter (mm)	1200

Node 70 Depth/Area Storage Structure

Base Inf Coefficient (m/hr)	0.00000	Safety Factor	2.0	Invert Level (m)	123.700
Side Inf Coefficient (m/hr)	0.00000	Porosity	1.00	Time to half empty (mins)	

Depth (m)	Area (m²)	Inf Area (m²)	Depth (m)	Area (m²)	Inf Area (m²)
0.000	230.4	0.0	1.500	758.9	0.0

Node 85 Depth/Area Storage Structure

Base Inf Coefficient (m/hr)	0.00000	Safety Factor	2.0	Invert Level (m)	124.100
Side Inf Coefficient (m/hr)	0.00000	Porosity	1.00	Time to half empty (mins)	0

Depth (m)	Area (m²)	Inf Area (m²)	Depth (m)	Area (m²)	Inf Area (m²)
0.000	505.2	0.0	1.500	1281.0	0.0

Results for 2 year Critical Storm Duration. Lowest mass balance: 99.78%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
15 minute winter	61	10	125.489	0.075	21.1	0.1863	0.0000	OK
15 minute winter	72	10	126.646	0.084	14.8	0.1744	0.0000	OK
15 minute winter	73	11	126.213	0.063	18.4	0.1278	0.0000	OK
15 minute winter	76	10	127.252	0.040	4.9	0.0583	0.0000	OK
15 minute winter	78	10	126.775	0.053	13.4	0.1225	0.0000	OK
15 minute winter	74	10	125.686	0.113	46.3	0.2066	0.0000	OK
15 minute winter	75	10	125.444	0.126	61.2	0.2331	0.0000	OK
15 minute winter	62	11	124.863	0.210	98.8	0.5233	0.0000	OK
15 minute winter	63	11	124.706	0.206	103.1	0.3974	0.0000	OK
15 minute winter	64	11	124.527	0.227	109.7	0.4624	0.0000	OK
15 minute winter	65	11	124.408	0.258	119.3	0.5780	0.0000	OK
15 minute winter	66	12	124.333	0.333	133.3	0.9219	0.0000	OK
480 minute winter	67	352	124.209	0.309	19.9	1.3514	0.0000	OK
480 minute winter	68	368	124.214	0.464	19.5	0.8190	0.0000	OK
15 minute winter	79	10	126.334	0.081	19.1	0.1897	0.0000	OK
15 minute winter	80	10	125.864	0.117	35.4	0.2369	0.0000	OK
15 minute winter	88	10	125.523	0.080	22.4	0.2051	0.0000	OK
15 minute winter	81	11	125.287	0.178	68.8	0.3079	0.0000	OK
15 minute summer	82	11	124.730	0.280	75.7	0.7462	0.0000	OK
15 minute summer	83	11	124.688	0.463	105.9	1.0928	0.0000	OK
15 minute winter	84	10	124.676	0.496	152.8	0.8762	0.0000	OK
480 minute winter	85	344	124.209	0.109	12.6	58.5830	0.0000	OK
480 minute winter	86	360	124.216	0.216	24.1	0.3822	0.0000	OK
480 minute winter	87	352	124.213	0.363	24.3	0.6418	0.0000	OK
480 minute winter	69	352	124.210	0.510	37.0	0.9014	0.0000	OK

Link Event (Upstream Depth)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
15 minute winter	61	1.000	62	20.7	1.533	0.131	0.4114	
15 minute winter	72	2.000	73	14.4	1.092	0.281	0.3572	
15 minute winter	73	2.001	74	18.2	0.928	0.063	0.5474	
15 minute winter	76	3.000	78	4.8	1.026	0.066	0.1003	
15 minute winter	78	3.002	74	13.0	1.566	0.067	0.2966	
15 minute winter	74	2.002	75	45.9	1.521	0.177	0.4577	
15 minute winter	75	2.003	62	61.3	1.807	0.236	1.1947	
15 minute winter	62	1.001	63	99.3	1.389	0.387	1.7323	
15 minute winter	63	1.002	64	103.7	1.377	0.366	1.9607	
15 minute winter	64	1.003	65	109.3	1.257	0.403	1.8504	
15 minute winter	65	1.004	66	117.0	1.072	0.511	3.2647	
15 minute winter	66	1.005	67	132.7	1.120	0.859	5.1195	
480 minute winter	67	1.006	68	19.5	0.707	0.082	3.7758	
480 minute winter	68	1.007	69	34.3	0.631	0.057	0.6640	
15 minute winter	79	4.000	80	18.8	1.122	0.279	0.5070	
15 minute winter	80	4.001	81	34.6	1.275	0.541	1.1548	
15 minute winter	88	5.000	81	22.2	0.987	0.275	0.3199	
15 minute winter	81	4.002	82	67.9	1.602	0.628	2.2813	
15 minute summer	82	4.003	83	86.0	1.105	0.446	5.2015	
15 minute summer	83	4.004	84	136.9	0.992	0.491	2.7648	
15 minute winter	84	4.005	85	174.7	2.366	0.433	2.9006	
480 minute winter	85	4.006	86	11.7	0.743	0.032	0.9951	
480 minute winter	86	4.007	87	23.8	0.517	0.054	2.1631	
480 minute winter	87	4.008	69	12.3	0.088	0.045	8.8630	
480 minute winter	69	1.008	70	32.6	0.341	0.088	1.8263	

Results for 2 year Critical Storm Duration. Lowest mass balance: 99.78%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
480 minute winter	70	352	124.209	0.559	32.6	164.1016	0.0000	SURCHARGED
15 minute summer	71	1	123.950	0.350	0.0	0.0000	0.0000	OK

Link Event (Upstream Depth)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
480 minute winter	70	Hydro-Brake®	71	10.9				272.4

Results for 30 year Critical Storm Duration. Lowest mass balance: 84.07%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
15 minute winter	61	10	125.516	0.102	40.1	0.2520	0.0000	OK
15 minute winter	72	10	126.685	0.123	28.0	0.2543	0.0000	OK
15 minute winter	73	10	126.236	0.086	35.0	0.1754	0.0000	OK
15 minute winter	76	10	127.267	0.055	9.3	0.0810	0.0000	OK
15 minute winter	78	10	126.794	0.073	25.4	0.1663	0.0000	OK
15 minute winter	74	10	125.739	0.166	88.5	0.3039	0.0000	OK
15 minute winter	75	10	125.498	0.180	116.8	0.3323	0.0000	OK
15 minute winter	62	12	125.122	0.469	188.8	1.1696	0.0000	SURCHARGED
15 minute winter	63	12	125.035	0.535	192.1	1.0321	0.0000	SURCHARGED
15 minute winter	64	12	124.932	0.632	201.3	1.2886	0.0000	SURCHARGED
15 minute winter	65	12	124.830	0.680	195.1	1.5252	0.0000	SURCHARGED
15 minute winter	66	11	124.682	0.682	221.3	1.8867	0.0000	SURCHARGED
480 minute winter	67	360	124.464	0.564	47.8	2.4675	0.0000	SURCHARGED
360 minute winter	68	240	124.811	1.061	499.7	1.8751	0.0000	SURCHARGED
15 minute winter	79	11	126.371	0.118	36.3	0.2766	0.0000	OK
15 minute winter	80	11	126.218	0.471	67.4	0.9521	0.0000	SURCHARGED
15 minute winter	88	11	125.654	0.211	42.6	0.5403	0.0000	OK
15 minute winter	81	11	125.550	0.441	122.4	0.7622	0.0000	SURCHARGED
15 minute winter	82	9	125.018	0.568	143.4	1.5115	0.0000	SURCHARGED
15 minute winter	83	9	124.897	0.672	215.7	1.5855	0.0000	SURCHARGED
15 minute winter	84	9	124.849	0.669	232.6	1.1821	0.0000	SURCHARGED
480 minute winter	85	352	124.392	0.292	32.2	169.9164	0.0000	OK
240 minute winter	86	184	124.434	0.434	72.0	0.7670	0.0000	OK
360 minute winter	87	280	124.457	0.607	40.0	1.0723	0.0000	SURCHARGED
60 minute winter	69	72	124.755	1.055	280.8	1.8643	0.0000	SURCHARGED

Link Event (Upstream Depth)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
15 minute winter	61	1.000	62	39.7	1.597	0.252	1.3503	
15 minute winter	72	2.000	73	27.4	1.282	0.535	0.5791	
15 minute winter	73	2.001	74	34.7	1.065	0.119	0.9058	
15 minute winter	76	3.000	78	9.1	1.234	0.126	0.1595	
15 minute winter	78	3.002	74	25.2	1.692	0.130	0.5550	
15 minute winter	74	2.002	75	87.2	1.772	0.335	0.7523	
15 minute winter	75	2.003	62	116.8	1.775	0.449	2.7327	
15 minute winter	62	1.001	63	184.5	1.537	0.719	3.8362	
15 minute winter	63	1.002	64	189.2	1.474	0.668	4.1240	
15 minute winter	64	1.003	65	179.4	1.311	0.662	3.3741	
15 minute winter	65	1.004	66	195.6	1.234	0.855	4.7222	
15 minute winter	66	1.005	67	218.8	1.381	1.417	6.8538	
480 minute winter	67	1.006	68	69.3	0.778	0.291	4.3589	
360 minute winter	68	1.007	69	-385.2	-1.783	-0.634	0.6902	
15 minute winter	79	4.000	80	35.9	1.258	0.532	0.9153	
15 minute winter	80	4.001	81	60.9	1.531	0.953	1.6855	
15 minute winter	88	5.000	81	40.2	1.136	0.498	0.5460	
15 minute winter	81	4.002	82	122.2	1.750	1.131	3.7784	
15 minute winter	82	4.003	83	165.3	1.366	0.856	6.6144	
15 minute winter	83	4.004	84	232.6	1.397	0.834	2.9138	
15 minute winter	84	4.005	85	262.6	2.683	0.651	3.2915	
480 minute winter	85	4.006	86	39.8	0.762	0.108	2.5446	
240 minute winter	86	4.007	87	34.5	0.616	0.078	3.6822	
360 minute winter	87	4.008	69	42.5	0.197	0.156	10.2479	
60 minute winter	69	1.008	70	185.6	1.224	0.500	1.8337	

Results for 30 year Critical Storm Duration. Lowest mass balance: 84.07%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
480 minute winter	70	352	124.381	0.731	219.0	240.0510	0.0000	SURCHARGED
15 minute summer	71	1	123.950	0.350	10.8	0.0000	0.0000	OK

Link Event (Upstream Depth)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
480 minute winter	70	Hydro-Brake®	71	11.0				351.2

Results for 100 year +40% CC Critical Storm Duration. Lowest mass balance: 70.47%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
15 minute winter	61	12	126.768	1.354	72.9	3.3513	0.0000	SURCHARGED
15 minute winter	72	12	127.147	0.585	50.9	1.2100	0.0000	SURCHARGED
15 minute winter	73	13	126.965	0.815	63.1	1.6550	0.0000	SURCHARGED
15 minute winter	76	10	127.288	0.076	17.0	0.1117	0.0000	OK
15 minute winter	78	13	126.998	0.277	46.2	0.6344	0.0000	OK
15 minute winter	74	13	126.944	1.371	156.4	2.5033	0.0000	SURCHARGED
15 minute winter	75	12	126.873	1.555	192.2	2.8708	0.0000	SURCHARGED
15 minute winter	62	12	126.666	2.013	252.5	5.0192	0.0000	SURCHARGED
15 minute winter	63	12	126.475	1.975	250.0	3.8121	0.0000	SURCHARGED
15 minute winter	64	12	126.258	1.958	266.6	3.9934	0.0000	SURCHARGED
15 minute winter	65	12	126.041	1.890	293.8	4.2422	0.0000	SURCHARGED
15 minute winter	66	12	125.705	1.705	338.2	4.7175	0.0000	FLOOD RISK
15 minute winter	67	12	125.116	1.216	446.7	5.3157	0.0000	SURCHARGED
960 minute winter	68	750	125.077	1.327	952.7	2.3456	199.3618	FLOOD
15 minute winter	79	11	127.978	1.725	66.0	4.0503	2.2843	FLOOD
15 minute winter	80	11	127.787	2.040	97.6	4.1269	0.9177	FLOOD
15 minute winter	88	11	126.991	1.548	77.3	3.9576	0.0000	FLOOD RISK
15 minute winter	81	11	126.665	1.556	185.9	2.6910	0.0000	SURCHARGED
15 minute winter	82	8	125.275	0.825	222.5	2.1963	0.0000	SURCHARGED
15 minute winter	83	8	125.114	0.889	309.9	2.0977	0.0000	SURCHARGED
15 minute winter	84	8	125.039	0.859	311.2	1.5175	0.0000	SURCHARGED
360 minute winter	85	344	124.763	0.663	68.6	449.5381	0.0000	SURCHARGED
480 minute winter	86	464	124.784	0.784	46.5	1.3847	0.0000	SURCHARGED
480 minute winter	87	464	124.792	0.942	47.5	1.6641	0.0000	SURCHARGED
720 minute winter	69	690	125.147	1.447	807.9	2.5564	291.0785	FLOOD

Link Event (Upstream Depth)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
15 minute winter	61	1.000	62	56.9	1.616	0.361	2.1470	
15 minute winter	72	2.000	73	49.4	1.417	0.965	1.0760	
15 minute winter	73	2.001	74	68.5	1.126	0.235	3.0123	
15 minute winter	76	3.000	78	16.7	1.454	0.231	0.4890	
15 minute winter	78	3.002	74	47.3	1.699	0.244	2.4570	
15 minute winter	74	2.002	75	141.4	1.784	0.543	1.6684	
15 minute winter	75	2.003	62	156.5	1.767	0.602	3.8669	
15 minute winter	62	1.001	63	239.2	1.568	0.932	3.8362	
15 minute winter	63	1.002	64	249.6	1.575	0.881	4.1240	
15 minute winter	64	1.003	65	266.8	1.684	0.984	3.3741	
15 minute winter	65	1.004	66	292.9	1.849	1.280	4.7222	
15 minute winter	66	1.005	67	334.8	2.113	2.168	6.8538	
15 minute winter	67	1.006	68	439.3	2.773	1.844	4.3589	
960 minute winter	68	1.007	69	-807.0	-3.736	-1.329	0.6902	
15 minute winter	79	4.000	80	45.4	1.267	0.673	1.1975	
15 minute winter	80	4.001	81	84.5	2.124	1.322	1.6855	
15 minute winter	88	5.000	81	68.7	1.728	0.850	0.5532	
15 minute winter	81	4.002	82	185.8	2.639	1.720	3.7883	
15 minute winter	82	4.003	83	223.4	1.480	1.157	6.6144	
15 minute winter	83	4.004	84	311.2	1.661	1.116	2.9138	
15 minute winter	84	4.005	85	319.6	2.853	0.793	3.3077	
360 minute winter	85	4.006	86	43.3	0.811	0.117	3.7028	
480 minute winter	86	4.007	87	46.6	0.558	0.106	3.9128	
480 minute winter	87	4.008	69	46.0	0.213	0.170	10.2479	
720 minute winter	69	1.008	70	-123.6	-0.572	-0.333	1.8337	

Results for 100 year +40% CC Critical Storm Duration. Lowest mass balance: 70.47%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
480 minute winter	70	416	124.737	1.087	159.6	430.2521	0.0000	SURCHARGED
15 minute summer	71	1	123.950	0.350	11.0	0.0000	0.0000	OK

Link Event (Upstream Depth)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
480 minute winter	70	Hydro-Brake®	71	11.0				345.1