

Bloor Homes		Page 0
Ashby Road Measham Swadlincote DE12 7JP		
Date 09/04/2026 09:22 File PH7A - FITCHETT STORM. ...	Designed by d_southa Checked by	
Innovyze	Network 2020.1.3	

STORM SEWER DESIGN by the Modified Rational Method

Design Criteria for Surface Network 8

Pipe Sizes STANDARD Manhole Sizes STANDARD

FSR Rainfall Model - England and Wales

Return Period (years)	2	PIMP (%)	100
M5-60 (mm)	20.000	Add Flow / Climate Change (%)	0
Ratio R	0.400	Minimum Backdrop Height (m)	0.200
Maximum Rainfall (mm/hr)	50	Maximum Backdrop Height (m)	1.500
Maximum Time of Concentration (mins)	30	Min Design Depth for Optimisation (m)	1.200
Foul Sewage (l/s/ha)	0.000	Min Vel for Auto Design only (m/s)	1.00
Volumetric Runoff Coeff.	0.750	Min Slope for Optimisation (1:X)	500

Designed with Level Soffits

Network Design Table for Surface Network 8

« - Indicates pipe capacity < flow

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
1.000	30.932	0.327	94.6	0.167	5.00	0.0	0.600	o	300	Pipe/Conduit	
1.001	17.048	0.253	67.4	0.081	0.00	0.0	0.600	o	300	Pipe/Conduit	
1.002	24.461	0.315	77.7	0.032	0.00	0.0	0.600	o	300	Pipe/Conduit	
1.003	16.291	0.265	61.5	0.011	0.00	0.0	0.600	o	450	Pipe/Conduit	
1.004	30.319	0.590	51.4	0.257	0.00	0.0	0.600	o	450	Pipe/Conduit	
1.005	14.528	0.258	56.2	0.000	0.00	0.0	0.600	o	450	Pipe/Conduit	
1.006	15.635	0.284	55.0	0.000	0.00	0.0	0.600	o	525	Pipe/Conduit	
1.007	30.561	0.110	277.8	0.066	0.00	0.0	0.600	o	525	Pipe/Conduit	
1.008	19.656	0.160	122.8	0.023	0.00	0.0	0.600	o	525	Pipe/Conduit	
2.000	42.890	0.416	103.1	0.184	5.00	0.0	0.600	o	300	Pipe/Conduit	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
1.000	50.00	5.32	102.116	0.167	0.0	0.0	0.0	1.62	114.3	22.6
1.001	50.00	5.47	101.789	0.248	0.0	0.0	0.0	1.92	135.6	33.6
1.002	50.00	5.70	101.536	0.280	0.0	0.0	0.0	1.79	126.2	37.9
1.003	50.00	5.80	101.071	0.291	0.0	0.0	0.0	2.60	413.0	39.4
1.004	50.00	5.98	100.806	0.548	0.0	0.0	0.0	2.84	451.9	74.2
1.005	50.00	6.07	100.216	0.548	0.0	0.0	0.0	2.72	431.8	74.2
1.006	50.00	6.15	99.883	0.548	0.0	0.0	0.0	3.02	654.8	74.2
1.007	50.00	6.53	99.570	0.614	0.0	0.0	0.0	1.34	289.8	83.1
1.008	50.00	6.70	99.460	0.637	0.0	0.0	0.0	2.02	437.2	86.2
2.000	50.00	5.46	100.555	0.184	0.0	0.0	0.0	1.55	109.4	24.9

Bloor Homes		Page 1
Ashby Road Measham Swadlincote DE12 7JP		
Date 09/04/2026 09:22 File PH7A - FITCHETT STORM. ...	Designed by d_southa Checked by	
Innovyze	Network 2020.1.3	

Network Design Table for Surface Network 8

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
2.001	26.139	0.153	170.8	0.120	0.00	0.0	0.600	o	300	Pipe/Conduit	
2.002	26.496	0.027	981.3	0.088	0.00	0.0	0.600	o	375	Pipe/Conduit	
3.000	48.145	0.207	232.6	0.115	5.00	0.0	0.600	o	525	Pipe/Conduit	
3.001	25.530	0.084	303.9	0.083	0.00	0.0	0.600	o	525	Pipe/Conduit	
2.003	15.475	0.209	74.0	0.007	0.00	0.0	0.600	o	525	Pipe/Conduit	
2.004	17.159	0.072	238.3	0.142	0.00	0.0	0.600	o	525	Pipe/Conduit	
2.005	13.568	0.027	502.5	0.138	0.00	0.0	0.600	o	525	Pipe/Conduit	
2.006	17.264	0.126	137.0	0.148	0.00	0.0	0.600	o	525	Pipe/Conduit	
1.009	41.865	0.075	556.0	0.047	0.00	0.0	0.600	o	525	Pipe/Conduit	
1.010	34.997	0.110	319.0	0.211	0.00	0.0	0.600	o	600	Pipe/Conduit	
1.011	32.331	0.546	59.2	0.074	0.00	0.0	0.600	o	600	Pipe/Conduit	
4.000	58.453	0.246	237.7	0.106	5.00	0.0	0.600	o	300	Pipe/Conduit	
1.012	6.746	0.124	54.4	0.164	0.00	0.0	0.600	o	600	Pipe/Conduit	
1.013	21.383	0.350	61.1	0.035	0.00	0.0	0.600	o	600	Pipe/Conduit	
1.014	13.269	0.160	82.9	0.030	0.00	0.0	0.600	o	600	Pipe/Conduit	
1.015	37.757	0.380	99.4	0.058	0.00	0.0	0.600	o	600	Pipe/Conduit	
1.016	47.054	1.100	42.8	0.112	0.00	0.0	0.600	o	600	Pipe/Conduit	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
2.001	50.00	5.82	100.139	0.304	0.0	0.0	0.0	1.20	84.8	41.2
2.002	50.00	6.60	99.911	0.392	0.0	0.0	0.0	0.57	63.0	53.1
3.000	50.00	5.55	100.025	0.115	0.0	0.0	0.0	1.46	317.0	15.6
3.001	50.00	5.88	99.818	0.198	0.0	0.0	0.0	1.28	277.0	26.8
2.003	50.00	6.70	99.734	0.597	0.0	0.0	0.0	2.61	564.0	80.8
2.004	50.00	6.90	99.525	0.739	0.0	0.0	0.0	1.45	313.1	100.1
2.005	50.00	7.12	99.453	0.877	0.0	0.0	0.0	0.99	214.8	118.8
2.006	50.00	7.27	99.426	1.025	0.0	0.0	0.0	1.91	413.9	138.8
1.009	50.00	8.01	99.300	1.709	0.0	0.0	0.0	0.94	204.1	231.5
1.010	50.00	8.44	99.150	1.920	0.0	0.0	0.0	1.36	383.9	260.0
1.011	50.00	8.61	99.040	1.994	0.0	0.0	0.0	3.17	895.9	270.0
4.000	50.00	5.96	99.040	0.106	0.0	0.0	0.0	1.02	71.8	14.3
1.012	50.00	8.65	98.494	2.264	0.0	0.0	0.0	3.31	935.2	306.5
1.013	50.00	8.76	98.370	2.299	0.0	0.0	0.0	3.12	882.0	311.3
1.014	50.00	8.84	98.020	2.329	0.0	0.0	0.0	2.68	756.5	315.4
1.015	50.00	9.10	97.860	2.387	0.0	0.0	0.0	2.44	690.8	323.3
1.016	50.00	9.31	97.480	2.499	0.0	0.0	0.0	3.73	1054.8	338.4

Bloor Homes		Page 2
Ashby Road Measham Swadlincote DE12 7JP		
Date 09/04/2026 09:22 File PH7A - FITCHETT STORM. ...	Designed by d_southa Checked by	
Innovyze	Network 2020.1.3	

Network Design Table for Surface Network 8

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
1.017	17.396	0.046	378.2	0.097	0.00	0.0	0.600	o	1000	Pipe/Conduit	
1.018	33.391	0.015	2226.1	0.092	0.00	0.0	0.600	o	600	Pipe/Conduit	
1.019	4.123	0.100	41.2	0.024	0.00	0.0	0.600	o	600	Pipe/Conduit	
1.020	20.322	0.300	67.7	0.000	0.00	0.0	0.600	o	600	Pipe/Conduit	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
1.017	50.00	9.48	96.380	2.596	0.0	0.0	0.0	1.71	1345.8	351.5
1.018	48.78	10.58	96.315	2.688	0.0	0.0	0.0	0.51	143.3	355.1
1.019	48.74	10.60	96.300	2.712	0.0	0.0	0.0	3.80	1074.4	358.0
1.020	48.46	10.71	96.200	2.712	0.0	0.0	0.0	2.96	837.4	358.0

Free Flowing Outfall Details for Surface Network 8

Outfall Pipe Number	Outfall Name	C. Level (m)	I. Level (m)	Min I. Level (m)	D,I (mm)	W (mm)
------------------------	-----------------	-----------------	-----------------	------------------------	-------------	-----------

1.020	S8053 - Headwall	97.000	95.900	0.000	0	0
-------	------------------	--------	--------	-------	---	---

Simulation Criteria for Surface Network 8

Volumetric Runoff Coeff	0.750	Additional Flow - % of Total Flow	0.000
Areal Reduction Factor	1.000	MADD Factor * 10m³/ha Storage	0.000
Hot Start (mins)	0	Inlet Coefficient	0.800
Hot Start Level (mm)	0	Flow per Person per Day (l/per/day)	0.000
Manhole Headloss Coeff (Global)	0.500	Run Time (mins)	60
Foul Sewage per hectare (l/s)	0.000	Output Interval (mins)	1

Number of Input Hydrographs	0	Number of Storage Structures	2
Number of Online Controls	1	Number of Time/Area Diagrams	0
Number of Offline Controls	0	Number of Real Time Controls	0

Synthetic Rainfall Details

Rainfall Model	FSR	Profile Type	Summer
Return Period (years)	2	Cv (Summer)	0.750
Region	England and Wales	Cv (Winter)	0.840
M5-60 (mm)	20.000	Storm Duration (mins)	30
Ratio R	0.400		

Bloor Homes		Page 3
Ashby Road Measham Swadlincote DE12 7JP		
Date 09/04/2026 09:22 File PH7A - FITCHETT STORM. ...	Designed by d_southa Checked by	
Innovyze	Network 2020.1.3	

Online Controls for Surface Network 8

Crown Vortex Valve® Manhole: S8052 Control Chamber, DS/PN: 1.020, Volume (m³): 15.0

Design Head (m) 1.400 Vortex Valve® Type R1 SW Only Invert Level (m) 96.200
Design Flow (l/s) 10.6 Diameter (mm) 123

Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)
0.100	2.1	1.200	9.8	3.000	15.5	7.000	23.7
0.200	4.6	1.400	10.6	3.500	16.7	7.500	24.5
0.300	4.9	1.600	11.3	4.000	17.9	8.000	25.3
0.400	5.7	1.800	12.0	4.500	19.0	8.500	26.1
0.500	6.3	2.000	12.7	5.000	20.0	9.000	26.8
0.600	6.9	2.200	13.3	5.500	21.0	9.500	27.6
0.800	8.0	2.400	13.9	6.000	21.9		
1.000	8.9	2.600	14.4	6.500	22.8		

©1982-2020 Innovyze

Bloor Homes

Ashby Road Measham
Swadlincote
DE12 7JP

Date 09/04/2026 09:22
File PH7A - FITCHETT STORM. ...

Innovyze

Page 5



Designed by d_southa
Checked by

Network 2020.1.3

Summary of Critical Results by Maximum Level (Rank 1) for Surface Network 8

Simulation Criteria

Areal Reduction Factor 1.000

Hot Start (mins) 0

Hot Start Level (mm) 0

Manhole Headloss Coeff (Global) 0.500

Foul Sewage per hectare (l/s) 0.000

Additional Flow - % of Total Flow 0.000

MADD Factor * 10m³/ha Storage 0.000

Inlet Coefficient 0.800

Flow per Person per Day (l/per/day) 0.000

Number of Input Hydrographs 0

Number of Online Controls 1

Number of Offline Controls 0

Number of Storage Structures 2

Number of Time/Area Diagrams 0

Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model

Region England and Wales

M5-60 (mm)

FSR

Cv (Summer)

20.000 Cv (Winter)

Ratio R 0.400

0.750

0.840

Margin for Flood Risk Warning (mm) 300.0

Analysis Timestep

DTS Status

DVD Status OFF

Fine Inertia Status OFF

ON

Profile(s)

Duration(s) (mins)

Return Period(s) (years)

Climate Change (%)

Summer and Winter

15, 30, 60, 120, 180, 240, 360, 480, 600, 720, 960, 1440

1, 30, 100

0, 0, 40

PN	US/MH Name	Storm	Return Period	Climate Change	First (X) Surcharge	First (Y) Flood
1.000	S8104 Jelson	15 Winter	100	+40%	100/15 Summer	
1.001	S8172 Jelson	15 Winter	100	+40%	100/15 Summer	
1.002	S8105 Jelson	15 Winter	100	+40%	100/15 Summer	
1.003	S8107 Jelson	15 Winter	100	+40%	100/15 Summer	
1.004	S8171 Jelson	15 Winter	100	+40%	100/15 Summer	
1.005	S8170 Jelson	15 Winter	100	+40%	100/15 Summer	
1.006	S8009 - Jelson Connection	15 Winter	100	+40%	30/15 Winter	100/15 Winter
1.007	S8010	15 Winter	100	+40%	30/15 Summer	100/15 Winter
1.008	S8011	15 Winter	100	+40%	30/15 Summer	
2.000	S8108 Jelson	15 Winter	100	+40%	30/15 Winter	100/15 Summer
2.001	S8109 Jelson	15 Winter	100	+40%	30/15 Summer	100/15 Summer
2.002	S8110 Jelson	15 Winter	100	+40%	30/15 Summer	
3.000	S8115 Jelson	15 Winter	100	+40%	100/15 Summer	
3.001	S8116 Jelson	15 Winter	100	+40%	30/15 Summer	
2.003	S8111 Jelson	15 Winter	100	+40%	30/15 Summer	
2.004	S8112 Jelson	15 Winter	100	+40%	30/15 Summer	
2.005	S8113 Jelson	15 Winter	100	+40%	30/15 Summer	
2.006	S8022 Jelson Connection	15 Winter	100	+40%	30/15 Summer	
1.009	S8023	15 Winter	100	+40%	30/15 Summer	
1.010	S8025	15 Winter	100	+40%	30/15 Summer	
1.011	S8026	15 Winter	100	+40%	100/15 Summer	

©1982-2020

Innovyze

Bloor Homes		Page 6
Ashby Road Measham Swadlincote DE12 7JP		
Date 09/04/2026 09:22 File PH7A - FITCHETT STORM. ...	Designed by d_southa Checked by	
Innovyze	Network 2020.1.3	

Summary of Critical Results by Maximum Level (Rank 1) for Surface Network 8

PN	US/MH Name	First (Z) Overflow	Overflow Act.	Water Level (m)	Surcharged Depth (m)	Flooded Volume (m³)	Flow / Cap.
1.000	S8104 Jelson			103.545	1.129	0.000	0.88
1.001	S8172 Jelson			103.301	1.212	0.000	1.15
1.002	S8105 Jelson			102.989	1.153	0.000	1.26
1.003	S8107 Jelson			102.495	0.974	0.000	0.51
1.004	S8171 Jelson			102.443	1.187	0.000	0.69
1.005	S8170 Jelson			102.130	1.464	0.000	0.92
1.006	S8009 - Jelson Connection			101.886	1.478	2.461	0.63
1.007	S8010			101.817	1.722	4.518	1.29
1.008	S8011			101.774	1.789	0.000	1.07
2.000	S8108 Jelson			102.563	1.708	3.484	0.98
2.001	S8109 Jelson			102.302	1.863	2.289	1.96
2.002	S8110 Jelson			101.936	1.650	0.000	4.65
3.000	S8115 Jelson			101.288	0.738	0.000	0.81
3.001	S8116 Jelson			101.468	1.125	0.000	1.02
2.003	S8111 Jelson			101.670	1.411	0.000	0.74
2.004	S8112 Jelson			101.738	1.688	0.000	1.11
2.005	S8113 Jelson			101.765	1.787	0.000	2.24
2.006	S8022 Jelson Connection			101.757	1.806	0.000	1.10
1.009	S8023			101.725	1.900	0.000	2.83
1.010	S8025			101.374	1.624	0.000	1.86
1.011	S8026			101.051	1.411	0.000	0.85

PN	US/MH Name	Overflow (l/s)	Half Drain Time (mins)	Pipe Flow (l/s)	Status	Level Exceeded
1.000	S8104 Jelson			91.9	FLOOD RISK	
1.001	S8172 Jelson			132.9	FLOOD RISK	
1.002	S8105 Jelson			142.2	SURCHARGED	
1.003	S8107 Jelson			147.8	SURCHARGED	
1.004	S8171 Jelson			267.2	SURCHARGED	
1.005	S8170 Jelson			264.9	FLOOD RISK	
1.006	S8009 - Jelson Connection			256.3	FLOOD	1
1.007	S8010			313.3	FLOOD	1
1.008	S8011			328.7	FLOOD RISK	
2.000	S8108 Jelson			100.1	FLOOD	3
2.001	S8109 Jelson			149.3	FLOOD	2
2.002	S8110 Jelson			187.9	SURCHARGED	
3.000	S8115 Jelson		7	228.9	FLOOD RISK	
3.001	S8116 Jelson			231.2	SURCHARGED	
2.003	S8111 Jelson			260.7	SURCHARGED	
2.004	S8112 Jelson			263.7	SURCHARGED	
2.005	S8113 Jelson			266.6	SURCHARGED	
2.006	S8022 Jelson Connection			298.2	FLOOD RISK	
1.009	S8023			505.4	FLOOD RISK	
1.010	S8025			597.0	SURCHARGED	
1.011	S8026			624.2	SURCHARGED	

Bloor Homes

Ashby Road Measham
Swadlincote
DE12 7JP

Date 09/04/2026 09:22
File PH7A - FITCHETT STORM. ...

Innovyze

Page 7



Designed by d_southa
Checked by

Network 2020.1.3

Summary of Critical Results by Maximum Level (Rank 1) for Surface Network 8

PN	US/MH Name	Storm	Return Period	Climate Change	First (X) Surcharge	First (Y) Flood
4.000	S8068	15 Winter	100	+40%	100/15 Summer	100/15 Winter
1.012	S8028	15 Winter	100	+40%	30/15 Summer	
1.013	S8029	15 Winter	100	+40%	100/15 Summer	
1.014	S8030	15 Winter	100	+40%	30/15 Summer	
1.015	S8031	15 Winter	100	+40%	100/15 Summer	
1.016	S8034	15 Winter	100	+40%	100/15 Summer	
1.017	S8037	15 Winter	100	+40%	100/15 Summer	100/600 Winter
1.018	S8039 - Headwall	1440 Summer	100	+40%	1/15 Winter	
1.019	S8051 - Headwall	1440 Summer	100	+40%		
1.020	S8052 Control Chamber	960 Winter	100	+40%	30/30 Summer	

PN	US/MH Name	First (Z) Overflow	Overflow Act.	Water Level (m)	Surcharged Depth (m)	Flooded Volume (m³)	Flow / Overflow Cap. (l/s)
4.000	S8068			100.792	1.452	1.856	0.88
1.012	S8028			100.744	1.650	0.000	2.08
1.013	S8029			100.341	1.371	0.000	1.23
1.014	S8030			99.903	1.283	0.000	1.80
1.015	S8031			99.435	0.975	0.000	1.26
1.016	S8034			98.860	0.780	0.000	0.84
1.017	S8037			98.092	0.712	0.000	0.99
1.018	S8039 - Headwall			97.334	0.419	0.000	0.57
1.019	S8051 - Headwall			96.900	0.000	0.000	0.29
1.020	S8052 Control Chamber			97.972	1.172	0.000	0.02

PN	US/MH Name	Half Drain Time (mins)	Pipe Flow (l/s)	Status	Level Exceeded
4.000	S8068		60.2	FLOOD	1
1.012	S8028		733.3	SURCHARGED	
1.013	S8029		731.8	SURCHARGED	
1.014	S8030		721.6	SURCHARGED	
1.015	S8031		736.7	SURCHARGED	
1.016	S8034		771.2	SURCHARGED	
1.017	S8037		783.9	FLOOD RISK	
1.018	S8039 - Headwall		100.5	SURCHARGED*	
1.019	S8051 - Headwall		101.3	SURCHARGED*	
1.020	S8052 Control Chamber		11.9	FLOOD RISK	

©1982-2020 Innovyze