
RICHMOND





Technical Data

Size (overall)	412 x 334mm
Minimum Pitch (The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this, please contact the Technical Solutions Hotline on 08708 702595)	22.5°
Maximum Pitch (subject to fixing specification)	90°
Minimum Headlap	112mm
Maximum Headlap	159mm
Minimum Gauge/Batten Spacing	253mm
Maximum Gauge/Batten Spacing	300mm
Hanging Length (approx.)	390mm
Cover	
Linear cover of 1 slate	300mm
Covering capacity at max. gauge	11.1 slates/m²
(all figures are net and do not allow for wastage)	
Weight per 1000*	4.58 tonnes
at max. gauge (approx.)	49kg/m²
per pallet, including pallet (approx.)	1.11 tonnes
Battens Required	
at max. gauge	3.33m/m²
Batten Size	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
Nail Size for Slates	50 x 3mm
Number of Slates/Pallet	240
Slates/Pack	40
Packs/Pallet	6

* All weights nominal

BS EN 490

Richmond provides a cost effective roofing solution where an authentic slate appearance is called for. Its unique design offers a thin leading edge and hidden interlock without compromising strength, durability and weathertightness.


● Through coloured



Slate Grey 30 ●



Farmhouse Red 39 ●



Breckland Brown 52 ●