

DATE: 21 March 2025
DESIGNER: Nick Smith
PROJECT No: 3125
PROJECT NAME: Leicester Road, Earl Shilton




Nick Smith Associates
Lighting to the end of the tunnel

Roadway Lighting Report

PREPARED BY: Nick Smith Associates Ltd
36 Foxbrook Drive, Chesterfield, S40 3JR
e: mail@nicksmithassociates.com
w: www.nicksmithassociates.com
t: 01246 229444
f: 01246 588604

Roadway Report Summary

Layout



Road Data

Calculation Grid	2015:EN13201 Illuminance
Width (m)	7.50
No. of Lanes	2
Road Surface	C2
Q0	0.07
Left Footpath(m)	2.00
Right Footpath(m)	2.00

Main Lighting

Column Data

Configuration	Single Sided Left
Spacing (m)	46.00
Height (m)	6.00
Tilt (deg)	0.00
Setback (m)	2.00
Outreach (m)	0.40
Overhang (m)	-1.60

Luminaire Data


Supplier	_My data
Type	S2 HWD2-#3K16 700-M1-CLO Gen 5
Lamp(s)	LED 3000K
LampFlux(klm)/Colour	3.62 3000/72
File Name	S2 HWD2-#3K16 700-M1-CLO (34W).ldt
Maintenance Factor	0.83
Lum. Int. Class	G2

Results


Main

Complies with P4

Eav	6.05
Emin	1.06
Emax	25.72
Emin/Emax	0.04
Emin/Eav	0.17
TI(%)	23.42




Energy performance indicators




Power Main Luminaire(W)	33.80
Parasitic Power(W)	0.00
Area(m ²)	345
Hours per Year	4100
Power Density(mW/lx/m ²)	16.19
AECI(kWh/m ²)	0.40

Polar Diagram

Main Luminaire S2 HWD2-#3K16 700-M1-CLO Gen 5




Horizontal Illuminance (lux)



Main Results

Eav	6.05
Emin	1.06
E _{max}	25.72
E _{min} /E _{max}	0.04
E _{min} /E _{av}	0.17
TI(%)	23.42


Horizontal Illuminance (lux)



Main Results

Eav	6.05
Emin	1.06
Emax	25.72
Emin/Emax	0.04
Emin/Eav	0.17
TI(%)	23.42

Horizontal Illuminance (lux)



Main Results

Eav	6.05
Emin	1.06
Emax	25.72
Emin/Emax	0.04
Emin/Eav	0.17
TI(%)	23.42

DATE: 21 March 2025
PROJECT No: 3125

DESIGNER: Nick Smith
PROJECT NAME: Leicester Road, Earl Shilton



Comparison Table

EN13201 Class: P4 Calculation Grid: 2015:EN13201 Illuminance Road Surface: C2 Q0: 0.07 No. of Lanes: 2 Total Width: 7.50
Configuration: Single Sided Left

No.	Luminaire	Lamp	Flux	MF	Spacing	Overhang	Height	Tilt	Eav	Emin	Emax	Emin/Emax	Emin/Eav	TI	Power Density	AECI
1	S2 HWD2-#3K16	LED 3000K	3.62	0.83	38.00	-1.60	6.00	0.00	7.32	2.04	25.66	0.08	0.28	20.23	16.19	0.49
2	S2 HWD2-#3K16	LED 3000K	3.62	0.83	39.00	-1.60	6.00	0.00	7.13	1.88	25.51	0.07	0.26	20.63	16.20	0.47
3	S2 HWD2-#3K16	LED 3000K	3.62	0.83	40.00	-1.60	6.00	0.00	6.96	1.77	25.77	0.07	0.25	21.03	16.19	0.46
4	S2 HWD2-#3K16	LED 3000K	3.62	0.83	41.00	-1.60	6.00	0.00	6.79	1.65	25.63	0.06	0.24	21.43	16.20	0.45
5	S2 HWD2-#3K16	LED 3000K	3.62	0.83	42.00	-1.60	6.00	0.00	6.62	1.52	25.49	0.06	0.23	21.84	16.20	0.44
6	S2 HWD2-#3K16	LED 3000K	3.62	0.83	43.00	-1.60	6.00	0.00	6.47	1.36	25.74	0.05	0.21	22.23	16.19	0.43
7	S2 HWD2-#3K16	LED 3000K	3.62	0.83	44.00	-1.60	6.00	0.00	6.32	1.26	25.61	0.05	0.20	22.63	16.20	0.42
8	S2 HWD2-#3K16	LED 3000K	3.62	0.83	45.00	-1.60	6.00	0.00	6.18	1.16	25.48	0.05	0.19	23.04	16.20	0.41
9	S2 HWD2-#3K16	LED 3000K	3.62	0.83	46.00	-1.60	6.00	0.00	6.05	1.06	25.72	0.04	0.17	23.42	16.19	0.40