

ducting express

Ducting Express Services Ltd
Trade House, 7 Claymill Road, Thurmaston, Leicester, LE4 9JJ



Circular spiral ducts standard length of 3m

Diameter	Area M ²	Circumference M	Material Thickness mm	Weight per 3 Meters
80	0.005	0.251	0.5	3.42
100	0.008	0.314	0.5	4.29
125	0.012	0.393	0.5	5.34
150	0.018	0.471	0.5	6.42
160	0.503	0.503	0.5	6.84
180	0.566	0.566	0.6	9.24
200	0.629	0.629	0.6	10.26
224	0.039	0.704	0.6	11.50
250	0.049	0.786	0.6	12.81
280	0.062	0.880	0.6	14.34
300	0.071	0.943	0.6	15.39
315	0.078	0.990	0.6	16.14
355	0.099	1.116	0.8	24.24
400	0.126	1.257	0.8	27.30
450	0.159	1.414	0.8	30.72
500	0.196	1.571	0.8	34.11
560	0.246	1.760	0.8	38.22
600	0.283	1.886	0.8	40.98
630	0.312	1.980	0.8	43.02
710	0.396	2.231	0.8	48.45
800	0.503	2.514	0.8	54.60
900	0.636	2.829	1.0	76.74

All above are nominal dimensions and weights

DW144 and is suitable for high,
manufactured from

Circular spiral ducts are manufactured from galvanised steel to comply
with HVCA specification DW144

Tel: 01455 616 444
E-mail: info@ducting-express.co.uk

Fax: 01455 616 442
www.ducting-express.co.uk