

wardell-armstrong.com

ENERGY AND CLIMATE CHANGE
ENVIRONMENT AND SUSTAINABILITY
INFRASTRUCTURE AND UTILITIES
LAND AND PROPERTY
MINING AND MINERAL PROCESSING
MINERAL ESTATES
WASTE RESOURCE MANAGEMENT



GLADMAN DEVELOPMENTS LTD

LAND OFF YORK CLOSE, MARKET BOSWORTH

AIR QUALITY ASSESSMENT

JULY 2024

DATE ISSUED: 4TH JULY 2024
JOB NUMBER: GM13363
REPORT NUMBER: 002
VERSION: V0.1
STATUS: FINAL

GLADMAN DEVELOPMENTS LTD

LAND OFF YORK CLOSE, MARKET BOSWORTH

AIR QUALITY ASSESSMENT

JULY 2024

PREPARED BY:

R Stiles Principal Environmental Scientist (Air
Quality)



APPROVED BY:

M T Walton Technical Director



This report has been prepared by Wardell Armstrong LLP with all reasonable skill, care and diligence, within the terms of the Contract with the Client. The report is confidential to the Client and Wardell Armstrong LLP accepts no responsibility of whatever nature to third parties to whom this report may be made known.

No part of this document may be reproduced without the prior written approval of Wardell Armstrong LLP.



Wardell Armstrong is the trading name of Wardell Armstrong LLP, Registered in England No. OC307138.

Registered office: Sir Henry Doulton House, Forge Lane, Etruria, Stoke-on-Trent, ST1 5BD, United Kingdom

UK Offices: Stoke-on-Trent, Birmingham, Cardiff, Carlisle, Edinburgh, Glasgow, Greater Manchester, Central Manchester
London, Newcastle upon Tyne, Sheffield, Truro. International Offices: Almaty

ENERGY AND CLIMATE CHANGE
ENVIRONMENT AND SUSTAINABILITY
INFRASTRUCTURE AND UTILITIES
LAND AND PROPERTY
MINING AND MINERAL PROCESSING
MINERAL ESTATES
WASTE RESOURCE MANAGEMENT

CONTENTS

EXECUTIVE SUMMARY	1
1 INTRODUCTION.....	2
1.1 Background.....	2
LEGISLATION AND POLICY CONTEXT	3
1.2 Relevant Air Quality Legislation and Guidance	3
1.3 Assessment Criteria.....	3
2 ASSESSMENT METHODOLOGY.....	5
2.1 Consultation and Scope of Assessment	5
2.2 Construction Phase Assessment	5
2.3 Operational Phase Assessment	6
2.4 Limitations and Uncertainties	9
3 BASELINE SITUATION	11
3.1 Hinckley and Bosworth Borough Council Local Air Quality Management.....	11
3.2 Background Air Pollutant Concentrations.....	11
3.3 Modelled Baseline Concentrations at Existing Sensitive Receptors	12
4 IMPACT ASSESSMENT	14
4.1 Construction Phase Assessment	14
4.2 Operational Phase Assessment.....	18
5 CONCLUSIONS.....	24
5.1 Construction Phase	24
5.2 Operational Phase	24
5.3 Summary	25

APPENDICES

Appendix A: Air Quality Legislation and Guidance
Appendix B: Methodology for Construction Phase Assessment
Appendix C: Methodology for Operational Phase Assessment
Appendix D: Operational Phase Assessment Sensitivity Analysis
Appendix E: Professional Experience of Assessors

DRAWINGS	TITLE	SCALE
GM13363-001	Existing and Proposed Sensitive Receptor Locations	1:10,000

EXECUTIVE SUMMARY

A detailed air quality assessment has been carried out to determine the potential air quality impacts associated with a proposed residential development at land off York Close, Market Bosworth.

The assessment has considered dust and particulate matter during the construction phase, and road traffic emissions during the operational phase. During the construction phase, the risk of dust soiling effects is classed as low for demolition and medium for earthworks, construction, and for trackout; the risk of human health effects is classed as negligible for demolition and low for earthworks, construction and for trackout. Mitigation measures have been proposed to further reduce any potential impacts based on best practice guidance.

For the operational phase assessment, annual mean NO₂, PM₁₀ and PM_{2.5} concentrations have been modelled at nineteen existing and two proposed receptor locations, using the most recent Emission Factor Toolkit available from DEFRA (EFT v12.0.1). In accordance with national guidance a sensitivity analysis has also been undertaken for NO₂ concentrations, in which Base Year background pollutant concentrations and vehicle emission factors are applied to the Opening/Future Years. This is considered to provide a conservative upper-bound to the assessment. Predicted annual mean concentrations have been compared to the relevant air quality objectives and target level.

The operational phase assessment and sensitivity analysis both conclude that the development will result in concentrations of NO₂, PM₁₀ and PM_{2.5} remaining below the air quality objectives/target values, both without and with the development for the proposed 2029 Opening/Future Year. The impact of the development is predicted to be negligible at all nineteen existing sensitive receptors that were assessed. Air quality effects are therefore considered to be 'not significant'.

The assessment has demonstrated that the proposed development will not lead to an unacceptable risk from air pollution, or to any breach in national objectives. Therefore, there are no material reasons in relation to air quality why the proposed scheme should not proceed.

1 INTRODUCTION

1.1 Background

- 1.1.1 Wardell Armstrong LLP has been commissioned by Gladman Developments Ltd to undertake an air quality assessment for a proposed residential development at land off York Close, Market Bosworth, Leicestershire.
- 1.1.2 It is our understanding that the proposals are for the construction of 105 residential dwellings and associated infrastructure.
- 1.1.3 The proposed development site is located to the south of Market Bosworth and is currently open, agricultural land. There is an existing large residential housing estate to the north and northeast, with open land surrounding the east, south and west of the site. Shenton Lane runs adjacent to the eastern boundary of the site. From information provided, access to site will be through an existing property at 35 York Close to the north, which is under the ownership of Gladman Developments Ltd and will be demolished during the construction of the proposed development.
- 1.1.4 This report details the results of an air quality assessment undertaken to accompany the planning application for the proposed development. The report discusses the potential air quality impacts of the additional road traffic generated by the proposed development. Air pollutant concentrations are considered at existing sensitive receptor locations in the vicinity of the proposed development, and at proposed sensitive receptor locations within the proposed development site.

LEGISLATION AND POLICY CONTEXT

1.2 Relevant Air Quality Legislation and Guidance

1.2.1 The air quality assessment has been undertaken in accordance with the following legislation and guidance:

- The Environment Act 1995, as amended 2021;
- Department of Environment, Food and Rural Affairs, The Air Quality Strategy for England, August 2023;
- The Air Quality Standards Regulations 2010;
- Department for Environment, Food and Rural Affairs, Local Air Quality Management Technical Guidance LAQM.TG(22), August 2022;
- The Institute of Air Quality Management (IAQM), Guidance on the Assessment of Dust from Demolition and Construction, January 2024;
- Ministry of Housing, Communities and Local Government, National Planning Policy Framework, December 2023; and
- Department for Communities and Local Government, Planning Practice Guidance: Air Quality, November 2019.

1.2.2 Further details of these documents are included in **Appendix A**.

1.3 Assessment Criteria

1.3.1 The relevant air quality objectives and limit values for this assessment are included within Table 1.

Table 1: Air Quality Objectives and Limit Values Relevant to the Assessment*			
Pollutant	Objective/Limit Value	Averaging Period	Obligation
Nitrogen Dioxide (NO ₂)	200µg/m ³ , not to be exceeded more than 18 times a year	1-hour mean	All local authorities
	40µg/m ³	Annual mean	All local authorities
Particulate Matter (PM ₁₀)	50µg/m ³ , not to be exceeded more than 35 times a year	24-hour mean	England, Wales and Northern Ireland
	40µg/m ³	Annual mean	England, Wales and Northern Ireland
Particulate Matter (PM _{2.5})	Limit Value of 20µg/m ³	Annual mean	England, Wales and Northern Ireland
*In accordance with the Air Quality Standards Regulations 2010			

1.3.2 Further details of where these objectives and limit values apply are detailed in **Appendix A.**

2 ASSESSMENT METHODOLOGY

2.1 Consultation and Scope of Assessment

2.1.1 The assessment methodology was sent to Hinckley and Bosworth Borough Council (HBBC) on 7th June 2024. Giles Rawdon, Environmental Health Officer at HBBC responded via email correspondence stating that “the methodology sounds fine”.

2.1.2 A summary of the consultation undertaken is provided in Table 2.

Table 2: Summary of Consultation		
Assessment Stage	Proposed Method	Response
Construction phase assessment to consider dust and fine particulate matter (PM ₁₀)	Qualitative assessment in accordance with Institute of Air Quality Management (IAQM) guidance	No objection to proposed methodology
Operational phase assessment to consider nitrogen dioxide (NO ₂) and fine particulate matter (PM ₁₀ and PM _{2.5})	Detailed assessment using the ADMS-Roads atmospheric dispersion model, in accordance with Environmental Protection UK (EPUK)/IAQM guidance, and with all predicted concentrations compared to air quality objectives/limit values	
	Meteorological data from the Nottingham East Midlands Meteorological Recording Station	
	Background concentrations from 2018-based DEFRA default maps	
	As there are no representative monitoring locations, it was proposed that a sensitivity analysis would be undertaken for NO ₂ concentrations, whereby Base Year background pollutant concentrations and vehicle emission factors would be applied to the Opening/Future Year scenarios	

2.2 Construction Phase Assessment

2.2.1 To assess the impacts associated with dust and particulate matter releases during the construction phase of the development, an assessment has been undertaken in accordance with guidance from the Institute of Air Quality Management (IAQM)¹. Further details of the construction assessment methodology are provided in **Appendix B**.

¹ Institute of Air Quality Management, Guidance on the Assessment of Dust from Demolition and Construction (v2.2), January 2024

- 2.2.2 The closest sensitive human receptors to where construction phase activities will take place are mostly residential and are detailed in Table 3. However, it should be noted that the assessment includes consideration of all sensitive receptors within 250m of the site boundary, in accordance with IAQM guidance.

Table 3: Closest Existing Sensitive Receptors Considered in the Construction Phase Assessment		
Receptor	Direction from the Site	Approximate Distance from the Site Boundary (m)
Residential receptors along York Close and Stanley Road	Northwest and north	<20m at closest point
Residential receptors along Northumberland Avenue and Shenton Lane	Northeast	<20m at closest point
Residential receptor along Shenton Lane	Southeast	Approximately 60m at closest point
Residential receptor along Shenton Lane	Southwest	Approximately 120m at closest point

- 2.2.3 There are no ecological receptors, or potentially dust sensitive statutory designated habitat sites, within 50m of the site and/or within 50m of the route(s) used by construction vehicles on the public highway, up to 250m from the site entrance(s). Ecological effects do not therefore need to be considered within this assessment.
- 2.2.4 The criteria used to assess the construction impact of the proposed development, and the associated significance of effects at existing sensitive receptors, are included in **Appendix B**.

2.3 Operational Phase Assessment

- 2.3.1 The air dispersion model ADMS-Roads (CERC, Version 5.0.1.3) has been used to assess the impacts associated with road traffic emissions during the operational phase assessment. The impacts have been assessed in accordance with guidance from Environmental Protection UK (EPUK) and the IAQM². Further details of the modelling and assessment methodology are provided in **Appendix C**.

² Moorcroft and Barrowcliffe et al, Land-Use Planning and Development Control: Planning for Air Quality (v1.2), January 2017

2.3.2 NO₂, PM₁₀ and PM_{2.5} concentrations have been predicted at existing and proposed sensitive receptors, as these are the pollutants considered most likely to exceed the objectives and limit values.

2.3.3 Air dispersion modelling has been carried out to estimate pollutant concentrations, due to road traffic emissions, for three assessment scenarios as follows:

- **Scenario 1:** 2023 Base Year;
- **Scenario 2:** 2029 Opening/Future Year, without the proposed development in place; and
- **Scenario 3:** 2029 Opening/Future Year, with the proposed development in place.

Existing Sensitive Receptors

2.3.4 Nineteen representative existing sensitive receptors (identified as ESR 1 to ESR 19) have been selected for consideration in the air quality assessment. These have been chosen based on their sensitivity and their proximity to roads which will be affected by development generated traffic.

2.3.5 Details of these receptors considered are provided in Table 4, and their locations are shown on drawing GM13363-001.

Table 4: Existing Sensitive Receptors Considered in Operational Phase Assessment				
Receptor	Address	Grid Reference		Receptor Type
		Easting	Northing	
ESR 1	Station Road	440220	303133	Residential
ESR 2	Weston Drive	440212	303073	Residential
ESR 3	Weston Drive	440197	302957	Residential
ESR 4	York Close	440058	302739	Residential
ESR 5	Station Road (The Market Bosworth School)	440428	303097	School
ESR 6	Warwick Lane	440455	303027	Residential
ESR 7	Southfield Way	440347	302952	Residential
ESR 8	Main Street	440605	303339	Residential
ESR 9	Main Street	440615	303190	Residential

Table 4: Existing Sensitive Receptors Considered in Operational Phase Assessment

Receptor	Address	Grid Reference		Receptor Type
		Easting	Northing	
ESR 10	Station Road (The Dixie Grammar School)	440574	303110	School
ESR 11	Station Place	440630	303043	Residential
ESR 12	Shenton Lane	440533	302941	Residential
ESR 13	Park Street	440681	303143	Residential
ESR 14	Rectory Lane	440661	303007	Residential
ESR 15	Sutton Lane	440644	302995	Residential
ESR 16	Shenton Lane	440373	302726	Residential
ESR 17	Sutton Lane	440687	301733	Residential
ESR 18	The Park	441482	303307	Residential
ESR 19	Bosworth Road	442254	303270	Residential

2.3.6 The criteria used to assess the operational impact of the proposed development, and the associated significance of effects at existing sensitive receptors, are included in **Appendix C**.

Proposed Sensitive Receptors

2.3.7 A number of proposed sensitive receptors (referred to as PR 1 and PR 2) have been selected within the development site boundary. These receptors are considered to be representative of the proposed residential areas which will be closest to the main existing source(s) of pollution. In this case, the main source is considered to be vehicle emissions from York Close and the Site Access Road.

2.3.8 Pollutant concentrations at the proposed receptors have been predicted for scenario 3 only (as detailed in paragraph 2.3.3). It is only necessary to consider the 'with development' scenarios for the proposed receptors as they will not experience any 'without development' conditions. It is therefore not necessary to consider the changes in pollutant concentrations at the proposed receptors.

2.3.9 Details of the proposed sensitive receptors are provided in Table 5, and their locations are shown on drawing GM13363-001.

Table 5: Proposed Sensitive Receptors Considered in the Operational Phase Assessment			
Receptor	Location	Grid Reference	
		Easting	Northing
PR 1	Locations considered to be representative of the proposed residential properties within site boundary	440073	302704
PR 2		440118	302563

2.3.10 The predicted concentrations at the proposed receptors have been assessed against the air quality objectives and limit values detailed in Table 1.

2.4 Limitations and Uncertainties

2.4.1 Air quality assessments make use of official sources of information (i.e. vehicle emission factors and background concentrations) which have historically been considered to be overly optimistic. Monitoring data collected by the UK Government and local authorities over the past few years has shown that annual mean NO₂ concentrations remained higher than previously expected (especially in roadside locations). This was widely thought to be due to the lower-than-expected decline in NO_x emissions from diesel vehicles (even as new Euro standards have been introduced), coupled with an overall increase in the number of diesel vehicles on the road.

2.4.2 The vehicle emission factors used in this assessment are from Defra's Emission Factor Toolkit (EFT v12.0.1)³, which is the most up-to-date version available.

2.4.3 A position statement was produced by the IAQM in 2018 which dealt specifically with the use of EFT v8.0 and the consideration of uncertainties in predicting future air quality⁴. The statement concluded that the approaches for dealing with this uncertainty should be decided on a case-by-case basis, but may include the use of a sensitivity test (i.e. where it is assumed that NO_x emissions will not reduce as quickly over time as within the EFT).

³ Defra Local Air Quality Management webpages (<https://laqm.defra.gov.uk/review-and-assessment/tools/emissions-factors-toolkit.html>)

⁴ Institute of Air Quality Management, Dealing with Uncertainty in Vehicle NO_x Emissions within Air Quality Assessments v1.1, July 2018

- 2.4.4 A later study provided evidence that EFT v9.0 may be relied upon to predict the ‘most likely’ future emissions reductions, as long as model verification has been undertaken using monitored data from 2016 or later⁵.
- 2.4.5 The IAQM has now withdrawn their 2019 position statement on the consideration of uncertainties in predicting future air quality⁶. A growing body of evidence suggests that the latest COPERT vehicle emission factors used in EFT v9.0 (and later) reflect real-world NO_x emissions more accurately. As a result, the IAQM judge that “an exclusively vehicle emissions-based sensitivity test is no longer necessary”. This is provided that the assessment has been verified using monitoring data from 2016 or later.
- 2.4.6 In accordance with Defra guidance, the air quality assessment has been carried out using EFT v12.0.1. As it has not been possible to undertake model verification, a sensitivity analysis has also been undertaken whereby base year background pollutant concentrations and vehicle emission factors have been applied to the Opening/Future Year scenarios. Further details of the sensitivity analysis, including the results, are provided in **Appendices C** and **D**, respectively.
- 2.4.7 Several steps have been taken to ensure the model is as accurate and representative as possible. These comprise:
- Consultation has been undertaken with HBBC to confirm their agreement with the methodology used within the assessment;
 - Detailed traffic data has been obtained from Ashley Helme Associates, the appointed transport consultant;
 - The latest Defra LAQM tools have been incorporated into the assessment;
 - Meteorological data, obtained from the Nottingham East Meteorological Recording Station has been incorporated into the assessment;
 - Road widths and the location of ESRs in relation to each road have been measured in detail to ensure greater accuracy within the model; and
 - A sensitivity analysis has been undertaken whereby 2023 Base Year background pollutant concentrations and vehicle emission factors have been applied to the 2029 Opening/Future Year.

⁵ Air Quality Consultants, Performance of Defra’s Emission Factor Toolkit 2013 – 2019, February 2020

⁶ Available on the Institute of Air Quality Management website (https://iaqm.co.uk/wp-content/uploads/2013/02/iaqm_uncertainty_vehicle_NOx_emission_withdrawn-02.pdf)

3 BASELINE SITUATION

3.1 Hinckley and Bosworth Borough Council Local Air Quality Management

- 3.1.1 The proposed development site is located within the administrative area of Hinckley and Bosworth Borough Council (HBBC), which is responsible for the management of local air quality.
- 3.1.2 There are currently no Air Quality Management Areas (AQMAs) declared within the administrative area of HBBC.
- 3.1.3 A review of the 2023 HBBC Annual Status Report (ASR, the latest report available online) indicates that there are no roadside or kerbside monitoring locations in proximity to the proposed development site.

3.2 Background Air Pollutant Concentrations

- 3.2.1 The air quality assessment needs to take into account background concentrations upon which the local, traffic derived pollution is superimposed.
- 3.2.2 Further review of the 2023 HBBC ASR indicates that there are currently no representative NO₂, PM₁₀ or PM_{2.5} background monitoring locations in the vicinity of the proposed development site. Therefore, background concentrations have been obtained from the 2018-based Defra default concentration maps, for the appropriate grid squares⁷.
- 3.2.3 The background pollutant concentrations used in this assessment are detailed in Table 6.

Table 6: Background Pollutant Concentrations Used in the Air Quality Assessment				
Grid Square (X, Y); Receptor(s)	Annual Mean Concentrations (µg/m ³)*			
	NO _x	NO ₂	PM ₁₀	PM _{2.5}
2023 Base Year				
440500, 303500; ESRs 1-2, 5-6, 8-11, 13-14	9.67	7.52	11.97	7.54
440500, 302500; ESRs 3-4, 7, 12, 15-16	9.41	7.33	12.47	7.66
440500, 301500; ESR 17	9.28	7.23	13.55	7.88

⁷ Accessed through the Defra Local Air Quality Management webpages (<http://laqm.defra.gov.uk/review-and-assessment/tools/background-maps.html>)

441500, 303500; ESR 18	9.43	7.35	11.96	7.54
442500, 303500; ESR 19	9.83	7.64	13.47	7.97
2029 Opening/Future Year				
440500, 303500; ESRs 1-2, 5-6, 8-11, 13-14	8.42	6.60	11.64	7.28
440500, 302500; ESRs 3-4, 7, 12, 15-16, PR 1-2	8.16	6.41	12.14	7.40
440500, 301500; ESR 17	8.04	6.32	13.23	7.62
441500, 303500; ESR 18	8.17	6.41	11.63	7.28
442500, 303500; ESR 19	8.41	6.59	13.14	7.71
<i>*Obtained from the Defra 2018-based background maps</i>				

3.3 Modelled Baseline Concentrations at Existing Sensitive Receptors

3.3.1 The baseline assessment (i.e. scenarios 1 and 2) has been carried out for the existing sensitive receptors considered, in accordance with Defra guidance (i.e. using EFT v12.0.1). The unadjusted NO₂, PM₁₀ and PM_{2.5} concentrations are detailed in Table 7.

Table 7: Predicted Unadjusted NO₂, PM₁₀ and PM_{2.5} Concentrations at Existing Sensitive Receptors for Scenarios 1 and 2

Receptor	Calculated Annual Mean Concentrations (µg/m ³)					
	Scenario 1: 2023 Base Year			Scenario 2: 2029 Opening/Future Year, Without Development		
	NO ₂ *	PM ₁₀	PM _{2.5}	NO ₂ *	PM ₁₀	PM _{2.5}
ESR 1	7.81	12.45	7.80	6.75	12.15	7.55
ESR 2	7.62	12.14	7.63	6.65	11.82	7.37
ESR 3	7.47	12.67	7.76	6.48	12.35	7.50
ESR 4	7.33	12.48	7.66	6.41	12.16	7.40
ESR 5	7.74	12.32	7.73	6.71	12.01	7.47

Table 7: Predicted Unadjusted NO₂, PM₁₀ and PM_{2.5} Concentrations at Existing Sensitive Receptors for Scenarios 1 and 2

Receptor	Calculated Annual Mean Concentrations (µg/m ³)					
	Scenario 1: 2023 Base Year			Scenario 2: 2029 Opening/Future Year, Without Development		
	NO ₂ *	PM ₁₀	PM _{2.5}	NO ₂ *	PM ₁₀	PM _{2.5}
ESR 6	7.65	12.17	7.65	6.66	11.84	7.39
ESR 7	7.42	12.61	7.73	6.45	12.28	7.47
ESR 8	7.67	12.22	7.67	6.67	11.89	7.41
ESR 9	7.76	12.35	7.74	6.72	12.02	7.48
ESR 10	8.15	12.85	8.01	6.92	12.54	7.75
ESR 11	7.78	12.37	7.76	6.73	12.05	7.49
ESR 12	7.41	12.60	7.73	6.45	12.27	7.46
ESR 13	7.76	12.36	7.75	6.72	12.03	7.48
ESR 14	7.77	12.31	7.73	6.72	11.98	7.46
ESR 15	7.45	12.64	7.75	6.47	12.31	7.49
ESR 16	7.37	12.54	7.70	6.43	12.22	7.43
ESR 17	7.24	13.56	7.89	6.32	13.24	7.63
ESR 18	7.53	12.24	7.70	6.51	11.90	7.43
ESR 19	8.38	14.49	8.52	6.96	14.15	8.24
*NO ₂ concentrations obtained by inputting predicted NO _x concentrations into the NO _x to NO ₂ calculator ⁸ in accordance with LAQM.TG(22)						

3.3.2 The results show that all predicted NO₂, PM₁₀ and PM_{2.5} concentrations are below the relevant objectives and limit values.

⁸ Defra Local Air Quality Management webpages (<http://laqm.defra.gov.uk/tools-monitoring-data/no-calculator.html>)

4 IMPACT ASSESSMENT

4.1 Construction Phase Assessment

Step 2 – Impact Assessment

- 4.1.1 In accordance with the IAQM guidance, the main activities to be considered during the construction phase of the proposed development are demolition, earthworks, construction and trackout.
- 4.1.2 Demolition is defined as the removal of an existing structure or structures. From information provided, access to site will be through an existing property at 35 York Close to the north of the site, which is under the ownership of Gladman and will be demolished during construction of the development.
- 4.1.3 Earthworks covers the processes of soil-stripping, ground-levelling, excavation and landscaping. Construction activities will focus on the proposed buildings, access roads car parking areas. Trackout is defined as the transport of dust and dirt by vehicles travelling from a construction site on to the public road network. This may occur through the spillage of dusty materials onto road surfaces or through the transportation of dirt by vehicles that have travelled over muddy ground on the site. This dust and dirt can then be deposited and re-suspended by other vehicles.

Step 2A

- 4.1.4 Step 2A of the assessment defines the potential dust emission magnitude from demolition, earthworks, construction and trackout in the absence of site-specific mitigation.
- 4.1.5 Examples of the criteria for the dust emission classes are detailed in **Appendix B**. The results of this step are detailed in Table 8.

Step 2B

- 4.1.6 Step 2B of the construction phase dust assessment defines the sensitivity of the area, taking into account the significance criteria detailed in **Appendix B**, for demolition, earthworks, construction and trackout. The sensitivity of the area to each activity is assessed for potential dust soiling, human health effects and ecological effects.
- 4.1.7 For demolition, there are currently between 1 and 10 receptors (residential) within 20m of where these activities may take place, which is assumed to be the site boundary for the purposes of this assessment.

4.1.8 For earthworks and construction, there are currently between 10 and 100 receptors (residential) within 20m of where these activities may take place, which is assumed to be the site boundary for the purposes of this assessment.

4.1.9 The routing of construction vehicles is unknown at this stage. Therefore, for the purposes of this assessment, worst case routing scenarios have been assumed for assessment of potential trackout impacts at nearby receptors.

4.1.10 As a result, for trackout, there are between 10 and 100 receptors (residential) within 20m of where trackout may occur for a distance of up to 250m from the site entrance.

Step 2C

4.1.11 Step 2C of the construction phase dust assessment defines the risk of impacts from each activity, by combining the dust emission magnitude with the sensitivity of the surrounding area.

4.1.12 The risk of dust impacts from each activity, with no mitigation in place, has been assessed in accordance with the criteria detailed in **Appendix B**. The results of this step are detailed in Table 8.

Summary of Step 2

4.1.13 Table 8 details the results of Step 2 of the construction phase assessment for human receptors.

Table 8: Construction Phase Dust Assessment for Human Receptors				
	Activity			
	Demolition	Earthworks	Construction	Trackout
Step 2A				
Dust Emission Magnitude	Small ^a	Medium ^b	Medium ^c	Medium ^d
Step 2B				
Sensitivity of Closest Receptors	High	High	High	High
Sensitivity of Area to Dust Soiling Effects	Medium	High	High	High
Sensitivity of Area to Human Health Effects	Low ^d	Low ^d	Low ^d	Low ^d
Step 2C				

Table 8: Construction Phase Dust Assessment for Human Receptors

	Activity			
	Demolition	Earthworks	Construction	Trackout
Dust Risk: Dust Soiling	Low Risk	Medium Risk	Medium Risk	Medium Risk
Dust Risk: Human Health	Negligible	Low Risk	Low Risk	Low Risk
a. Total building volume estimated to be less than 12,000m³. b. Total site area estimated to be between 18,000m² and 110,000m². c. Total building volume estimated to be between 12,000m³ and 75,000m³ with potentially dusty construction materials (e.g., concrete). c. Number of construction phase vehicles estimated to be between 20 and 50 movements per day. d. Background annual mean PM₁₀ concentration is taken from the LAQM Defra default concentration maps, for the appropriate grid square for 2024.				

Step 3 – Mitigation

4.1.14 During the construction phase, the implementation of effective mitigation measures will substantially reduce the potential for nuisance dust and particulate matter to be generated.

4.1.15 Step 2C of the assessment has identified that the risk of dust soiling and human health effects is not negligible for all the activities and therefore site-specific mitigation will need to be implemented to ensure dust effects from these activities will be not significant.

Recommendations for Site-Specific Mitigation

4.1.16 Specific mitigation relating to dust control may be in the form of construction best practices or could include a dust management plan. Recommendations for mitigation within the IAQM guidance include:

- Soft strip inside buildings before demolition;
- Ensure effective water suppression is used during demolition operations. Handheld sprays are more effective than hoses attached to equipment as the water can be directed to where it is needed;
- Re-vegetate earthworks and exposed areas/soil stockpiles to stabilise surfaces as soon as practicable;
- Protection of surfaces and exposed material from winds until disturbed areas are sealed and stable;

- Dampening down of exposed stored materials, which will be stored as far from sensitive receptors as possible;
- Ensure sand and other aggregates are stored in bunded areas and are not allowed to dry out, unless this is required for a particular process, in which case ensure that appropriate additional control measures are in place;
- Avoidance of activities that generate large amounts of dust during windy conditions;
- Ensure bulk cement and other fine powder materials are delivered in enclosed tankers and stored in silos with suitable emission control systems to prevent escape of material and overfilling during delivery;
- Avoid dry sweeping of large areas;
- Use water-assisted dust sweeper(s) on the access and local roads, to remove, as necessary, any material tracked out of the site. This may require the sweeper being continuously in use;
- Ensure vehicles entering and leaving the site are covered to prevent escape of materials during transport;
- Implement a wheel washing system (with rumble grids to dislodge accumulated dust and mud prior to leaving the site where reasonably practicable);
- Minimisation of vehicle movements and limitation of vehicle speeds – the slower the vehicle speeds, the lower the dust generation;
- Ensure there is an adequate area of hard surfaced road between the wheel wash facility and the site exit, wherever the site size and layout permits; and
- Access gates to be located at least 10m from receptors, where possible.

4.1.17 All dust and air quality complaints should be recorded and appropriate measures be taken to identify causes and reduce emissions in a timely manner. Exceptional incidents which cause dust and/or emissions, and the action taken to resolve the situation, should be recorded in a log book and made available to HBBC on request.

4.1.18 It is recognised that the final design solutions will be developed with the input of the Contractor to maximise construction efficiencies, to use modern construction techniques and sustainable materials and to incorporate the particular skills and experience offered by the appointed contractor.

Step 4 – Residual Effects

4.1.19 Step 4 of the construction phase dust assessment has been undertaken to determine the significance of the dust effects arising from demolition, earthworks, construction and trackout associated with the proposed development.

4.1.20 The implementation of effective mitigation measures during the construction phase, such as those detailed in Step 3, will substantially reduce the potential for nuisance dust and particulate matter to be generated and any residual impact should be **not significant**.

4.2 Operational Phase Assessment

Existing Sensitive Human Receptors

4.2.1 The impact assessment has been carried out for the representative existing sensitive receptors considered (i.e. ESR 1 to ESR 19) using EFT v12.0.1. In accordance with national guidance, a sensitivity analysis, whereby 2023 Base Year background pollutant concentrations and vehicle emission factors have been applied to the 2029 Opening/Future Year, has also been undertaken (the results of which are included in **Appendix D**). This applies to NO₂ concentrations only.

4.2.2 Table 9 details the predicted NO₂ concentrations for the 2029 Opening/Future Year, for both the ‘Without Development’ and ‘With Development’ scenarios, in accordance with Defra guidance (i.e. using EFT v12.0.1). The impact has been assessed in accordance with the descriptors included in **Appendix C**.

Table 9: Predicted Unadjusted NO₂ Concentrations at Existing Sensitive Receptors for Scenarios 2 and 3 – Using the Emission Factor Toolkit v12.0.1					
Receptor	Calculated Annual Mean NO₂ Concentrations (µg/m³)^a				
	Without Development	With Development		Concentration Change as Percentage of AQAL	Impact^b
		Concentration	Percentage in Relation to AQAL		
ESR 1	6.75	6.76	<75%	<0.5%	Negligible
ESR 2	6.65	6.66	<75%	<0.5%	Negligible
ESR 3	6.48	6.49	<75%	<0.5%	Negligible
ESR 4	6.41	6.44	<75%	<0.5%	Negligible
ESR 5	6.71	6.71	<75%	<0.5%	Negligible
ESR 6	6.66	6.67	<75%	<0.5%	Negligible

Table 9: Predicted Unadjusted NO₂ Concentrations at Existing Sensitive Receptors for Scenarios 2 and 3 – Using the Emission Factor Toolkit v12.0.1

Receptor	Calculated Annual Mean NO ₂ Concentrations (µg/m ³) ^a				
	Without Development	With Development		Concentration Change as Percentage of AQAL	Impact ^b
		Concentration	Percentage in Relation to AQAL		
ESR 7	6.45	6.46	<75%	<0.5%	Negligible
ESR 8	6.67	6.67	<75%	<0.5%	Negligible
ESR 9	6.72	6.72	<75%	<0.5%	Negligible
ESR 10	6.92	6.93	<75%	<0.5%	Negligible
ESR 11	6.73	6.74	<75%	<0.5%	Negligible
ESR 12	6.45	6.45	<75%	<0.5%	Negligible
ESR 13	6.72	6.72	<75%	<0.5%	Negligible
ESR 14	6.72	6.72	<75%	<0.5%	Negligible
ESR 15	6.47	6.47	<75%	<0.5%	Negligible
ESR 16	6.43	6.43	<75%	<0.5%	Negligible
ESR 17	6.32	6.32	<75%	<0.5%	Negligible
ESR 18	6.51	6.51	<75%	<0.5%	Negligible
ESR 19	6.96	6.97	<75%	<0.5%	Negligible
<i>a. NO₂ concentrations obtained by inputting predicted NO_x concentrations into the NO_x to NO₂ calculator, in accordance with LAQM.TG(22)</i> <i>b. Assessed using the Impact Descriptors from the EPUK/IAQM guidance, included in Appendix C. Changes of less than 0.5% should be described as negligible</i>					

4.2.3 Table 10 details the PM₁₀ concentrations for the 2029 Opening/Future Year, for both the ‘Without Development’ and ‘With Development’ scenarios. The impact has been assessed in accordance with the descriptors included in **Appendix C**.

Table 10: Predicted Unadjusted PM₁₀ Concentrations at Existing Sensitive Receptors for Scenarios 2 and 3 – Using the Emission Factor Toolkit v12.0.1

Receptor	Calculated Annual Mean PM ₁₀ Concentrations (µg/m ³)				
	Without Development	With Development		Concentration Change as Percentage of AQAL	Impact ^a
		Concentration	Percentage in Relation to AQAL		
ESR 1	12.15	12.17	<75%	<0.5%	Negligible
ESR 2	11.82	11.84	<75%	<0.5%	Negligible
ESR 3	12.35	12.38	<75%	<0.5%	Negligible
ESR 4	12.16	12.24	<75%	<0.5%	Negligible
ESR 5	12.01	12.02	<75%	<0.5%	Negligible
ESR 6	11.84	11.86	<75%	<0.5%	Negligible
ESR 7	12.28	12.30	<75%	<0.5%	Negligible
ESR 8	11.89	11.89	<75%	<0.5%	Negligible
ESR 9	12.02	12.03	<75%	<0.5%	Negligible
ESR 10	12.54	12.58	<75%	<0.5%	Negligible
ESR 11	12.05	12.06	<75%	<0.5%	Negligible
ESR 12	12.27	12.29	<75%	<0.5%	Negligible
ESR 13	12.03	12.04	<75%	<0.5%	Negligible
ESR 14	11.98	11.99	<75%	<0.5%	Negligible
ESR 15	12.31	12.32	<75%	<0.5%	Negligible
ESR 16	12.22	12.22	<75%	<0.5%	Negligible
ESR 17	13.24	13.24	<75%	<0.5%	Negligible
ESR 18	11.90	11.92	<75%	<0.5%	Negligible
ESR 19	14.15	14.18	<75%	<0.5%	Negligible
a. Assessed using the Impact Descriptors from the EPUK/IAQM guidance, included in Appendix C. Changes of less than 0.5% should be described as negligible					

4.2.4 Table 11 details the PM_{2.5} concentrations for the 2029 Opening/Future Year, for both the ‘Without Development’ and ‘With Development’ scenarios. The impact has been assessed in accordance with the descriptors included in **Appendix C**.

Table 11: Predicted Unadjusted PM_{2.5} Concentrations at Existing Sensitive Receptors for Scenarios 2 and 3 – Using the Emission Factor Toolkit v12.0.1

Receptor	Calculated Annual Mean PM _{2.5} Concentrations (µg/m ³)				
	Without Development	With Development		Concentration Change as Percentage of AQAL	Impact ^a
		Concentration	Percentage in Relation to AQAL		
ESR 1	7.55	7.56	<75%	<0.5%	Negligible
ESR 2	7.37	7.38	<75%	<0.5%	Negligible
ESR 3	7.50	7.52	<75%	<0.5%	Negligible
ESR 4	7.40	7.45	<75%	<0.5%	Negligible
ESR 5	7.47	7.48	<75%	<0.5%	Negligible
ESR 6	7.39	7.40	<75%	<0.5%	Negligible
ESR 7	7.47	7.48	<75%	<0.5%	Negligible
ESR 8	7.41	7.41	<75%	<0.5%	Negligible
ESR 9	7.48	7.48	<75%	<0.5%	Negligible
ESR 10	7.75	7.77	<75%	<0.5%	Negligible
ESR 11	7.49	7.50	<75%	<0.5%	Negligible
ESR 12	7.46	7.47	<75%	<0.5%	Negligible
ESR 13	7.48	7.49	<75%	<0.5%	Negligible
ESR 14	7.46	7.47	<75%	<0.5%	Negligible
ESR 15	7.49	7.49	<75%	<0.5%	Negligible
ESR 16	7.43	7.44	<75%	<0.5%	Negligible
ESR 17	7.63	7.63	<75%	<0.5%	Negligible
ESR 18	7.43	7.44	<75%	<0.5%	Negligible
ESR 19	8.24	8.25	<75%	<0.5%	Negligible
a. Assessed using the Impact Descriptors from the EPUK/IAQM guidance, included in Appendix C. Changes of less than 0.5% should be described as negligible					

4.2.5 The results of the assessment show that all predicted NO₂, PM₁₀ and PM_{2.5} concentrations, in all scenarios considered, are below the relevant objectives and limit values. Therefore, the assessment predicts that the proposed development will have a negligible impact on concentrations of NO₂, PM₁₀ and PM_{2.5} at all nineteen existing sensitive receptors considered.

Proposed Sensitive Human Receptors

- 4.2.6 Pollutant concentrations have been modelled for proposed receptors for the 2029 Opening/Future Year 'With Development' scenario, in accordance with Defra guidance (i.e. using EFT v12.0.1), as detailed in Table 12.

Table 12: Predicted Unadjusted NO₂, PM₁₀ and PM_{2.5} Concentrations at Proposed Sensitive Receptors for Scenario 3 – Using Emission Factor Toolkit v12.0.1			
Proposed Receptor	Calculated Annual Mean Concentrations (µg/m³)		
	NO₂	PM₁₀	PM_{2.5}
PR 1	6.43	12.21	7.43
PR 2	6.42	12.18	7.42

- 4.2.7 The results of the assessment show that predicted NO₂, PM₁₀ and PM_{2.5} concentrations, at the proposed receptor locations, are below the relevant objectives and limit values.

Assessment of Significance for Human Receptors

- 4.2.8 The significance of the overall effects of the proposed development has been assessed in accordance with the EPUK/IAQM guidance. This assessment is based on professional judgement and details of the assessor's experience is included in **Appendix E**.
- 4.2.9 The results of a no improvement sensitivity analysis are provided in **Appendix D** to account for any potential uncertainty in air quality reporting.
- 4.2.10 The assessment of significance has taken into account a number of factors, including:
- Baseline pollutant concentrations in 2023 and 2029 are below the relevant annual mean objectives and limit values at all existing receptors considered;
 - The assessment predicts a negligible impact on concentrations of NO₂, PM₁₀ and PM_{2.5} at all existing sensitive receptors considered, with the development in place;
 - NO₂, PM₁₀ and PM_{2.5} concentrations within the proposed development site are predicted to be below the relevant objectives and limit values; and

- The sensitivity analysis included in **Appendix D**, predicts negligible impact on concentrations of NO₂ at all existing sensitive receptors considered, with the development in place.

4.2.11 Based on the above factors, in accordance with the EPUK/IAQM guidance, the air quality effect of the proposed development is considered to be **not significant**.

Recommendations for Mitigation

4.2.12 The impact of the proposed development is predicted to be not significant for human receptors. However, mitigation measures will assist in reducing any potential impact and general best practice measures in relation to air quality could be implemented.

4.2.13 Electric Vehicle (EV) charging points are now standard for all new residential developments with associated car parking spaces⁹.

4.2.14 However, additional mitigation measures could include the use of low NO_x boilers and the implementation of a green travel plan.

⁹ The Building Regulations 2010, "Infrastructure for the Charging of Electric Vehicles" (2021)

5 CONCLUSIONS

5.1 Construction Phase

5.1.1 The construction phase assessment has been undertaken to determine the risk and significance of dust and fine particulate matter effects from demolition, earthworks, construction and trackout associated with the proposed development, in accordance with guidance published by the IAQM.

5.1.2 With site specific mitigation measures in place, the significance of dust and fine particulate effects from demolition, earthworks, construction and trackout is considered to be **not significant**.

5.2 Operational Phase

Existing Sensitive Receptors

5.2.1 An air quality assessment has been undertaken to consider the potential impact of development generated vehicles on air quality at nineteen existing sensitive human receptors.

5.2.2 The assessment has been undertaken in accordance with Defra guidance, by using the latest vehicle emission factors from EFT v12.0.1. In addition, a sensitivity analysis has been undertaken for NO₂ concentrations, in which Base Year pollutant concentrations and vehicle emission factors have been used in the Opening/Future Year scenarios.

5.2.3 Pollutant concentrations in 2029, with the development in place, are below the relevant annual mean objectives and limit values at the receptors considered.

5.2.4 The assessment and sensitivity analysis both predict that the development will have a negligible impact on concentrations of NO₂, PM₁₀ and PM_{2.5} at all nineteen existing sensitive receptors considered in 2029. The effect of the proposed development on human receptors is therefore considered to be **not significant**.

Proposed Sensitive Receptors

5.2.5 The assessment and sensitivity analysis have also predicted pollutant concentrations at two proposed receptors within the development site.

5.2.6 Predicted NO₂, PM₁₀ and PM_{2.5} concentrations are below the annual mean air quality objective and limit value concentrations, for 2029, at the proposed sensitive receptors considered. Air quality effects within the site are, therefore, considered to be **not significant**.

Recommendations for Mitigation

- 5.2.7 The impact of the proposed development is predicted to be not significant. However, mitigation measures will assist in reducing any potential impact and general best practice measures in relation to air quality could be implemented. EV charging points are now standard for all new residential developments with associated car parking spaces. Therefore, additional mitigation measures could include the use of low NO_x boilers and the implementation of a green travel plan.

5.3 Summary

- 5.3.1 The assessment has demonstrated that the proposed development will not lead to an unacceptable risk from air pollution, nor will it lead to any breach of national objectives as required by national policy. There are no material reasons in relation to air quality why the proposed scheme should not proceed.

APPENDICES

Appendix A: Air Quality Legislation and Guidance

National Air Quality Strategy

- A.1 The Environment Act 1995 requires the UK government to prepare a national Air Quality Strategy. The first UK strategy was published in March 1997, setting out policies for the management of ambient air quality. This was subsequently updated in 2007¹.
- A.2 The 2007 strategy establishes the framework for air quality management in England, Scotland, Wales and Northern Ireland. Air quality standards and objectives are set out for eight pollutants which may potentially occur at levels that give cause for concern. The strategy also provides details of the role that local authorities are required to take in working towards improvements in air quality, known as the Local Air Quality Management (LAQM) regime.
- A.3 Defra published an updated air quality strategy in April 2023, and updated in August 2023². The revised strategy supersedes the 2007 strategy in England only and provides a framework to enable local authorities to make the best use of their powers and make improvements for their communities. It also includes guidance on the new fine particulate matter targets for England.

Air Quality Standards and Objectives

- A.4 Air quality standards and objectives are set out in the strategy for the following pollutants: nitrogen dioxide (NO₂), sulphur dioxide (SO₂), carbon monoxide (CO), lead (Pb), fine particulate matter (PM₁₀), benzene (C₆H₆), 1, 3-butadiene (C₄H₆) and ozone (O₃).
- A.5 Objectives for each pollutant, except O₃, were first given statutory status in the Air Quality Regulations 2000³ and Air Quality (Amendment) Regulations 2002⁴. These objectives are defined in the strategy as:

“the maximum ambient concentration not to be exceeded, either without exception or with a permitted number of exceedances, within a specified timescale.”

¹ Department of Environment, Food and Rural Affairs, The Air Quality Strategy for England, Scotland, Wales and Northern Ireland. July 2007

² Department of Environment, Food and Rural Affairs, Air quality strategy: framework for local authority delivery, August 2023

³ The Air Quality Regulations 2000. SI No 928

⁴ The Air Quality (Amendment) Regulations 2002

- A.6 EU limit values, set out within the Ambient Air Quality Directive 2008/50/EC⁵ (i.e. the CAFE Directive), were transposed into UK legislation on 11th June 2011 as The Air Quality Standards Regulations 2010. These are mostly the same as the air quality objectives in terms of concentrations; however, there are differences in determining how compliance is achieved. Although the UK is no longer part of the EU, no changes have yet been made to the objectives and limit values used in the management and assessment of air quality.
- A.7 Whilst there is no specific objective for PM_{2.5} in England and Wales, a limit value of 20µg/m³ is referred to in the regulations, which has been adopted for use in this assessment (as recommended by the LAQM Helpdesk). An objective has been set for PM_{2.5} in Scotland since early 2016. The Environment Act 2021 sets out a requirement to establish a target objective for PM_{2.5}, and this has now been set through the Environmental Targets (Fine Particulate Matter) (England) Regulations 2023. Annual mean concentrations of PM_{2.5} must now meet a target of 10 µg/m³ across England by 2040.
- A.8 Examples of where these objectives and limit values apply are detailed in the Defra LAQM Technical Guidance document LAQM.TG(22)⁶ and are included in Table A1.

Table A1: Examples of Where the Air Quality Objectives Should Apply		
Averaging Period	Objectives Should Apply at:	Objectives Should Generally Not Apply at:
Annual mean	All locations where members of the public might be regularly exposed. Building façades of residential properties, schools, hospitals, care homes, etc.	Building facades of offices or other places of work where members of the public do not have regular access. Hotels, unless people live there as their permanent residence. Gardens of residential properties. Kerbside sites (as opposed to locations at the building façade), or any other location where public exposure is expected to be short term
24-hour mean and 8-hour mean	All locations where the annual mean objectives would apply, together with hotels. Gardens of residential properties ^a	Kerbside sites (as opposed to locations at the building façade), or any other location where public exposure is expected to be short term

⁵ Directive 2008/50/EC of the European Parliament and of the Council of 21 May 2008 on ambient air quality and cleaner air for Europe

⁶ Department for Environment, Food and Rural Affairs, Local Air Quality Management Technical Guidance LAQM.TG(22), August 2022

Table A1: Examples of Where the Air Quality Objectives Should Apply

Averaging Period	Objectives Should Apply at:	Objectives Should Generally Not Apply at:
1-hour mean	All locations where the annual mean and 24 and 8-hour objectives apply. Kerbside sites (e.g. pavements of busy shopping streets). Those parts of car parks and railway stations etc. which are not fully enclosed, where members of the public might reasonably be expected to spend one hour or more. Any outdoor locations to which the public might reasonably be expected to spend one hour or longer	Kerbside sites where public would not be expected to have regular access
15-minute mean	All locations where members of the public might reasonably be exposed for a period of 15 minutes or longer	
<i>^a. Such locations should represent parts of the garden where relevant public exposure is likely, for example where there is seating or play areas. It is unlikely that relevant public exposure to pollutants would occur at the extremities of the garden boundary, or in front gardens, although local judgement should always be applied</i>		

Local Air Quality Management

- A.9 LAQM legislation in the Environment Act 1995 requires local authorities to conduct the periodic review and assessments of air quality. These aim to identify all those areas where the objectives are being, or are likely to be, exceeded. Where exceedances are likely to occur, local authorities are required to declare an Air Quality Management Area (AQMA).
- A.10 LAQM.TG(22) presents a streamlined approach for LAQM in England and Scotland; however, Northern Ireland is still considering changes to LAQM and therefore works according to the previous regime.
- A.11 The Welsh Government amended the LAQM regime in Wales in 2017 by issuing new statutory policy guidance in order to bring the system into line with the Well-being of Future Generations (Wales) Act 2015⁷. This aims to achieve compliance with the national air quality objectives in specific hotspots and to reduce exposure to pollution more widely, so as to achieve the greatest public health benefit.

⁷ Well-being of Future Generations (Wales) Act 2015 (anaw 2)

- A.12 Local authorities in England are required to produce Annual Status Reports (ASRs), and in Scotland and Wales, Annual Progress Reports (APRs). These replace all other reports which previously had to be submitted including Updating and Screening Assessments, Progress Reports and Detailed Assessments (which would be produced to assist with an AQMA declaration).
- A.13 Local authorities now have the option of a fast track AQMA declaration option. This allows more expert judgement to be used and removes the need for a Detailed Assessment where a local authority is confident of the outcome. Detailed Assessments should however still be used if there is any doubt.
- A.14 As part of the UK Government's requirement to improve air quality, selected local authorities in England are also currently investigating the feasibility of setting up Clean Air Zones (CAZs). These are areas where targeted action and co-ordinated resources aim to improve air quality within an urban setting, in order to achieve compliance with the EU limit values within the shortest possible time.
- A.15 The first CAZs were implemented in Bath in March 2021, and in Birmingham in June 2021. Since then CAZ's have also been declared in Bradford, Bristol, Portsmouth, Sheffield and Tyneside (Newcastle and Gateshead). In addition, the London Ultra Low Emission Zone (ULEZ) has now been expanded to incorporate all London Boroughs. The Greater Manchester CAZ, due to be introduced from 30 May 2022, has been delayed and is currently under review.

National Planning Policy Framework

- A.16 The National Planning Policy Framework (NPPF)⁸, introduced in March 2012 and most recently updated in December 2023, requires that:

"Planning policies and decisions should sustain and contribute towards compliance with relevant limit values or national objectives for pollutants, taking into account the presence of AQMAs and CAZs, and the cumulative impacts from individual sites in local areas.

Opportunities to improve air quality or mitigate impacts should be identified, such as through traffic and travel management, and green infrastructure provision and enhancement. So far as possible these opportunities should be considered at plan-making stage, to ensure a strategic approach and limit the need for issues to be

⁸ Ministry of Housing, Communities and Local Government, National Planning Policy Framework, December 2023

reconsidered when determining individual applications.

Planning decisions should ensure that any new development in AQMAs and CAZs is consistent with the local air quality action plan.”

Planning Practice Guidance

- A.17 The Planning Practice Guidance (PPG)⁹, updated in November 2019, states that whether or not air quality is relevant to a planning decision will depend on the proposed development and its location. Concerns could arise if the development is likely to generate air quality impacts in an area where air quality is known to be poor. They could also arise where the development is likely to adversely impact upon the implementation of air quality strategies and action plans and/or, in particular, lead to a breach of EU legislation (including that applicable to wildlife).
- A.18 Where a proposed development is anticipated to give rise to concerns about air quality, an appropriate assessment needs to be carried out. Where the assessment concludes that the proposed development (including mitigation) will not lead to an unacceptable risk from air pollution, prevent sustained compliance with national objectives or fail to comply with the requirements of the Habitats Regulations, then the local authority should proceed to decision with appropriate planning conditions and/or obligations.

⁹ Department for Communities and Local Government. Planning Practice Guidance: Air Quality, November 2019

Appendix B: Methodology for Construction Phase Assessment

Institute of Air Quality Management Guidance

- B.1 The methodology for the construction phase dust assessment is set out in guidance from the Institute of Air Quality Management (IAQM)¹⁰.

Step 1

- B.2 Step 1 is to screen the requirement for a more detailed assessment. The guidance states that an assessment will normally be required where there are existing sensitive human receptors within 250m of the site boundary and/or within 50m of the route(s) used by construction vehicles on the public highway, up to 250m from the site entrance(s).
- B.3 With regards to ecological receptors, the guidance states that an assessment will normally be required where there are existing receptors within 50m of the site boundary and/or within 50m of the route(s) used by construction vehicles on the public highway, up to 250m from the site entrance(s).
- B.4 Where any of these criteria are met, it is necessary to proceed to Step 2.

Step 2

- B.5 Step 2 determines the potential risk of dust arising in sufficient quantities to cause annoyance and/or health or ecological impacts. The risk is related to:
- The activities being undertaken (demolition, number of vehicles and plant etc);
 - The duration of these activities;
 - The size of the site;
 - The meteorological conditions (wind speed, direction and rainfall);
 - The proximity of receptors to the activity;
 - The adequacy of the mitigation measures applied to reduce or eliminate dust; and
 - The sensitivity of receptors to dust.
- B.6 The risk of dust impacts is determined using four risk categories: negligible, low, medium and high risk. A site is allocated to a risk category based upon the following two factors (known as Step 2A and Step 2B).

¹⁰ Institute of Air Quality Management, Guidance on the Assessment of Dust from Demolition and Construction (v2.2), January 2024

B.7 Step 2A assesses the scale and nature of the works which determines the potential dust emission magnitude as small, medium or large. Examples of how the magnitude may be defined are included in Table B1.

Table B1: Determining the Dust Emission Magnitude of Construction Phase Activities			
Activity	Dust Emission Class		
	Large	Medium	Small
Demolition	Total building volume >75,000m ³ ; Potentially dusty construction material (e.g. concrete); On-site crushing and screening; Demolition activities >12m above ground level	Total building volume 12,000 - 75,000m ³ ; Potentially dusty construction material; Demolition activities 6-12m above ground level	Total building volume <12,000m ³ ; Construction material with low potential for dust release (e.g. metal cladding or timber), demolition activities <6m above ground, demolition during wetter months
Earthworks	Total site area >110,000m ² ; Potentially dusty soil type (e.g. clay, which will be prone to suspension when dry due to small particle size); >10 heavy earth moving vehicles active at any one time; Formation of bunds >6m in height;	Total site area 18,000-110,000m ² ; Moderately dusty soil type (e.g. silt); 5-10 heavy earth moving vehicles active at any one time; Formation of bunds 3-6m in height;	Total site area <18,000m ² ; Soil type with large grain size (e.g. sand); <5 heavy earth moving vehicles active at any one time; Formation of bunds <4m in height;
Construction	Total building volume >75,000m ³ ; On-site concrete batching; Sandblasting	Total building volume 12,000 - 75,000m ³ ; Potentially dusty construction material (e.g. concrete); On-site concrete batching	Total building volume <12,000m ³ ; Construction material with a low potential for dust release (e.g. metal cladding or timber)
Trackout	>50 HDV (>3.5t) outward movements ^a in any one day ^b ; Potentially dusty surface material (e.g. high clay content); Unpaved road length >100m	20-50 HDV (>3,5t) outward movements ^a in any one day ^b ; Moderately dusty surface material (e.g. high clay content); Unpaved road length 50-100m	<20 HDV (>3.5t) outward movements ^a in any one day ^b ; Surface material with low potential for dust release; Unpaved road length <50m
<i>a. A vehicle movement is a one way journey i.e. from A to B, and excludes the return journey</i> <i>b. HDV movements during a construction project may vary over its lifetime, and the number of movements is the maximum not the average</i>			

B.8 **Step 2B** considers the sensitivity of the area to dust impacts which is defined as low, medium or high. The sensitivity categories for different types of receptors are described in Table B2.

Table B2: Sensitivity Categories for Dust Soiling, Human Health and Ecological Effects			
Sensitivity Category	Dust Soiling Effects	Health effects of PM ₁₀	Ecological Effects
High	Users can reasonably expect to enjoy a high level of amenity; Appearance, aesthetics or value of a property would be diminished; Examples include dwellings, museums and other culturally important collections, medium and long term car parks and car show rooms	Locations where members of the public are exposed over a period of time relevant to the air quality objective for PM ₁₀ ; Examples include residential properties, hospitals, schools, and residential care homes	Locations with an international or national designation and the designated features may be affected by dust soiling; Locations where there is a community of a particularly dust sensitive species; Examples include a Special Area of Conservation with dust sensitive features
Medium	Users would expect to enjoy a reasonable level of amenity, but would not reasonably expect to enjoy the same level of amenity as in their home; The appearance, aesthetics or value of their property could be diminished; People or property wouldn't reasonably be expected to be continuously present or regularly for extended periods of time; Examples include parks and places of work	Locations where people are exposed as workers and exposure is over a period of time relevant to the air quality objective for PM ₁₀ ; Examples include office and shop workers but will generally not include workers occupationally exposed to PM ₁₀	Locations where there is a particularly important plant species, where its dust sensitivity is uncertain or unknown; Locations with a national designation where the features may be affected by dust deposition; Examples include a Site of Special Scientific Interest with dust sensitive features
Low	Enjoyment of amenity would not reasonably be expected; Property would not be diminished in appearance, aesthetics or value; People or property would be expected to be present only for limited periods of time;	Locations where human exposure is transient; Examples include public footpaths, playing fields, parks and shopping streets	Locations with a local designation where the features may be affected by dust deposition; Examples include a Local Nature Reserve with dust sensitive features

Table B2: Sensitivity Categories for Dust Soiling, Human Health and Ecological Effects

Sensitivity Category	Dust Soiling Effects	Health effects of PM ₁₀	Ecological Effects
	Examples include playing fields, farmland (unless commercially-sensitive horticultural), footpaths, short term car parks and roads		

B.9 Based on the sensitivity of individual receptors, the overall sensitivity of the area to dust soiling, human health and ecological effects is then determined using the criteria detailed in Tables B3 to B5, respectively.

Table B3: Sensitivity of the Area to Dust Soiling Effects on People and Property^{ab}

Receptor Sensitivity	Number of Receptors	Distance from Source (m) ^c			
		<20m	<50m	<100m	<250m
High	>100	High	High	Medium	Low
	10-100	High	Medium	Low	Low
	1-10	Medium	Low	Low	Low
Medium	>1	Medium	Low	Low	Low
Low	>1	Low	Low	Low	Low

a. The sensitivity to the area should be derived for each of the four activities

b. Estimate the total number of receptors within the stated distance. Only the highest level of sensitivity from the table needs to be considered

c. For trackout, distances should be measured from the side of the roads used by construction traffic. Without site specific mitigation, trackout may occur for up to 500m from large sites, 200m from medium sites and 50m from small sites, measured from the site exit. The impact declines with distance from the site and it is only necessary to consider trackout impacts up to 50m from the edge of the road

Table B4: Sensitivity of the Area to Human Health Impacts^{ab}

Receptor Sensitivity	Annual Mean PM ₁₀ Concentration ^c	Number of Receptors ^d	Distance from Source (m) ^e			
			<20m	<50m	<100m	<250m
High	>32µg/m ³	>100	High	High	High	Medium
		10-100	High	High	Medium	Low
		1-10	High	Medium	Low	Low

Table B4: Sensitivity of the Area to Human Health Impacts^{ab}

Receptor Sensitivity	Annual Mean PM ₁₀ Concentration ^c	Number of Receptors ^d	Distance from Source (m) ^e			
			<20m	<50m	<100m	<250m
	28-32µg/m ³	>100	High	High	Medium	Low
		10-100	High	Medium	Low	Low
		1-10	High	Medium	Low	Low
	24-28µg/m ³	>100	High	Medium	Low	Low
		10-100	High	Medium	Low	Low
		1-10	Medium	Low	Low	Low
	<24µg/m ³	>100	Medium	Low	Low	Low
		10-100	Low	Low	Low	Low
		1-10	Low	Low	Low	Low
Medium	>32µg/m ³	>10	High	Medium	Low	Low
		1-10	Medium	Low	Low	Low
	28-32µg/m ³	>10	Medium	Low	Low	Low
		1-10	Low	Low	Low	Low
	24-28µg/m ³	>10	Low	Low	Low	Low
		1-10	Low	Low	Low	Low
	<24µg/m ³	>10	Low	Low	Low	Low
		1-10	Low	Low	Low	Low
Low	-	>1	Low	Low	Low	Low

a. The sensitivity to the area should be derived for each of the four activities

b. Estimate the total number of receptors within the stated distance. Only the highest level of sensitivity from the table needs to be considered

c. Most straightforwardly taken from the national background maps, but should also take account of local sources. The values are based on 32µg/m³ being the annual mean concentration at which an exceedance of the 24-hour mean objective is likely in England, Wales and Northern Ireland. In Scotland, there is an annual mean objective of 18µg/m³

d. In the case of high sensitivity receptors with high occupancy (such as schools or hospitals) approximate the number of people likely to be present. In the case of residential dwellings, just include the number of properties

e. For trackout, distances should be measured from the side of the roads used by construction traffic

Table B5: Sensitivity of the Area to Ecological Impacts^{ab}

Receptor Sensitivity	Distance from the Source (m) ^c	
	<20	<50
High	High	Medium
Medium	Medium	Low
Low	Low	Low
a. The sensitivity to the area should be derived for each of the four activities b. Only the highest level of sensitivity from the table needs to be considered c. For trackout, distances should be measured from the side of the roads used by construction traffic		

B.10 These two factors are combined in **Step 2C** to determine the risk of dust impacts with no mitigation applied.

B.11 The risk of dust effects is determined for four types of construction phase activities, with each activity being considered separately. If a construction phase activity is not taking place on the site, then it does not need to be assessed. The four types of activities to be considered are:

- Demolition;
- Earthworks;
- Construction; and
- Trackout.

B.12 The risk of dust being generated by demolition activities at the site is determined using the criteria in Table B6.

Table B6: Risk of Dust Impacts for Demolition

Sensitivity of Area	Dust Emission Magnitude		
	Large	Medium	Small
High	High Risk	Medium Risk	Medium Risk
Medium	High Risk	Medium Risk	Low Risk
Low	Medium Risk	Low Risk	Negligible

B.13 The risk of dust being generated by earthworks and construction at the site is determined using the criteria in Table B7.

Table B7: Risk of Dust Impacts for Earthworks and Construction			
Sensitivity of Area	Dust Emission Magnitude		
	Large	Medium	Small
High	High Risk	Medium Risk	Low Risk
Medium	Medium Risk	Medium Risk	Low Risk
Low	Low Risk	Low Risk	Negligible

- B.14 The risk of dust being generated by trackout at the site is determined using the criteria in Table B8.

Table B8: Risk of Dust Impacts for Trackout			
Sensitivity of Area	Dust Emission Magnitude		
	Large	Medium	Small
High	High Risk	Medium Risk	Low Risk
Medium	Medium Risk	Low Risk	Negligible
Low	Low Risk	Low Risk	Negligible

Step 3

- B.15 Step 3 of the assessment determines the site-specific mitigation required for each of the activities, based on the risk determined in Step 2. Mitigation measures are detailed in guidance published by the Greater London Authority¹¹, recommended for use outside the capital by LAQM guidance, and the IAQM guidance document itself. Professional judgement should be used to determine the type and scale of mitigation measures required.
- B.16 If the risk is classed as negligible, no mitigation measures beyond those required by legislation will be necessary.

Step 4

- B.17 Step 4 assesses the residual effect, with mitigation measures in place, to determine whether or not these are significant.

¹¹ Greater London Authority, The Control of Dust and Emissions from Construction and Demolition: Supplementary Planning Guidance, 2014

Professional Judgement

- B.18 The IAQM guidance makes reference to the use of professional judgement when assessing the risks of dust and fine particulate matter from demolition and construction sites. Details of the experience of the personnel involved with the project are provided in **Appendix E**.

Appendix C: Methodology for Operational Phase Assessment

Air Dispersion Modelling Inputs

- C.1 The air dispersion model ADMS-Roads (CERC, Version 5.0.1.3) has been used to assess the potential air quality impacts associated with development-generated road traffic emissions. This dispersion model is widely used and accepted for the purpose of undertaking assessments to support both planning and Environmental Permit applications.

Traffic Flow Data

- C.2 The ADMS-Roads model requires the input of detailed road traffic flow data for those routes which may be affected by the proposed development. Traffic flow data has been provided for this project by Ashley Helme Associates, the appointed transport consultants for the project. The study extent of the model is shown in Figure C.1.




Figure C.1: Study Extent of Air Dispersion Model. The roads modelled in the assessment can be seen in blue, whilst the receptor locations are green (*'Reproduced from Ordnance Survey Maps © Crown Copyright All Rights Reserved Licence No. 0100031673'*)

C.3 Data has been provided as 24-hour Annual Average Daily Traffic (AADT) flows, with HGV percentages. No average speed information was available and therefore speed limits have been used, with a reduction to 20kph in locations where congestion or the slowing down of vehicles would be expected.

C.4 The traffic flow data used in the assessment is included in Table C1.

Table C1: 24-hour AADT traffic data used in the assessment						
Link Name	Scenario 1: 2023 Verification and Base Year		Scenario 2: 2029 Opening/ Future Year, Without Development		Scenario 3: 2029 Opening/Future Year, With Development	
	LGV	HGV	LGV	HGV	LGV	HGV
Station Road (W)	7377	120	8272	134	8450	137
Station Road (E)	7248	118	8091	132	8211	134
Weston Drive	1084	0	1189	0	1492	0
Market Place (N)	4394	99	4643	104	4766	107
Market Place (S)	4219	82	4459	86	4591	89
Shenton Lane	999	24	1056	25	1118	26
Station Road (W)	7988	155	8845	171	9158	177
Back Lane	702	4	742	4	742	4
Main Street	6481	119	7037	129	7265	133
Market Place	4499	92	4970	101	5078	104
Main Street (N)	2776	37	2933	39	2973	39
Main Street (S)	6454	118	6819	125	7062	129
Park Street	4521	92	4777	97	4979	102
Park Street	4457	96	4710	101	4912	105
The Park	8040	147	8494	156	8830	162
Rectory Lane	4138	76	4372	80	4505	83
Market Place (N)	4219	82	4459	86	4591	89
Rectory Lane	4151	85	4386	90	4519	92
Sutton Lane	88	0	93	0	93	0
Shenton Lane (E)	956	25	1009	26	1071	27
Shenton Lane (W)	937	15	990	16	1091	18
Warwick Lane	710	7	749	8	914	9
Back Lane	1679	83	1774	88	1774	88
Station Road (E)	7969	163	8825	180	9138	186
Southfield Way	1115	7	1206	7	1402	8
Station Road (W)	7189	117	8028	131	8149	132
A447 Ashby Road (N)	10720	400	11326	423	11406	426

Table C1: 24-hour AADT traffic data used in the assessment

Link Name	Scenario 1: 2023 Verification and Base Year		Scenario 2: 2029 Opening/ Future Year, Without Development		Scenario 3: 2029 Opening/Future Year, With Development	
	LGV	HGV	LGV	HGV	LGV	HGV
B585 Bosworth Lane	5902	145	6236	153	6407	158
A447 Ashby Road (S)	14878	429	15720	453	15802	455
Bosworth Road	7114	153	7518	161	7853	168
Site Access	-	-	-	-	789	9

Vehicle Emission Factors

- C.5 The air quality assessment has used vehicle emission factors calculated using the Emissions Factor Toolkit (EFT) version 12.0.1, released in December 2023. This is the most up-to-date version of the EFT currently available.
- C.6 As discussed in the section 3.4 of the report, in accordance with the latest guidance from the IAQM, a sensitivity analysis does not need to be undertaken where model verification has been possible using data from later than 2016¹².
- C.7 In this case, due to the lack of council owned monitoring locations in the vicinity of the proposed development, it has not been possible to undertake model verification. Therefore, a sensitivity analysis has also been undertaken whereby Base Year background pollutant concentrations and vehicle emission factors have been applied to Opening/Future Year scenarios.
- C.8 It is considered that the results of the sensitivity analysis provide a conservative upper-bound to the assessment. The results are included in **Appendix D**.

Street Canyons

- C.9 LAQM.TG(22) states that '*street canyons can generally be defined as narrow streets where the height of buildings on both sides of the road is greater than the road width*'. The principal effects of a street canyon on the dispersion of pollution from a road source are:

¹² Available on the Institute of Air Quality Management website (https://iaqm.co.uk/wp-content/uploads/2013/02/iaqm_uncertainty_vehicle_NOx_emission_withdrawn-02.pdf)

- Pollution being channelled along the canyon;
- Pollution being dispersed across the canyon by circulating flow at road height;
- Pollutants being trapped in recirculation regions;
- Pollutants leaving the canyon between gaps in the buildings;
- Pollutants leaving the canyon from the canyon top; and
- Pollutants leaving the canyon from the downstream end of the canyon.

C.10 The model has not included any street canyons as there are none along the roads included in the study network.

Meteorological Data

C.11 The meteorological data used in the air quality modelling has been obtained from ADM Limited and is from the Nottingham East Meteorological Recording Station, covering the period between 1st January and 31st December 2023.

C.12 The Nottingham East Meteorological Recording Station is located approximately 23km northwest of the proposed development and is considered to be the most representative of the conditions at the proposed development, due to its relative location and similar altitude.

C.13 The 2023 wind rose for the Nottingham East Meteorological Recording Station is shown in Figure C2.




Figure C.2: 2023 Wind Rose for the Nottingham East Meteorological Station

Dispersion and Meteorological Site Characteristics

- C.14 The characteristics for the dispersion site and meteorological sites, included in the ADMS-Roads model, are detailed in Table C2.

Table C2: Dispersion and Meteorological Site Characteristics		
Setting	Dispersion Site	Meteorological Site
Surface Roughness	0.5m	0.02m
Surface Albedo	0.23	0.23
Minimum Monin-Obukhov Length	30m	1m
Priestley-Taylor Parameter	1	1

NO_x to NO₂ Conversion

- C.15 In accordance with the guidance within LAQM.TG(22), the ADMS-Roads model has been run to predict the road-contribution NO_x concentrations for each receptor location. These have then been converted to NO₂ concentrations using the Defra NO_x to NO₂ calculator¹³.

Model Validation and Verification

- C.16 LAQM.TG(22) refers to model validation as *“the general comparison of modelled results against monitoring data carried out by model developers”*. ADMS-Roads is widely accepted by regulatory authorities for use in this type of assessment.
- C.17 Model verification is used to check the performance of the model at a local level. The verification of the ADMS-Roads air dispersion model is achieved by modelling concentration(s) at existing monitoring location(s) in the vicinity of the proposed development, and comparing the modelled concentration(s) with the measured concentration(s).
- C.18 Following review of the 2023 HBBC ASR, it is understood there are no representative NO₂, PM₁₀ or PM_{2.5} monitoring locations situated along roads where traffic flow data is available. Therefore, it has not been possible to carry out model verification for any modelled concentrations.

¹³ Defra Local Air Quality Management web pages [<http://laqm.defra.gov.uk/tools-monitoring-data/no-calculator.html>]

Assessment Criteria

Assessing the Impact of a Proposed Development on Human Receptors

- C.19 Guidance has been prepared by Environmental Protection UK (EPUK) and the IAQM¹⁴ with relation to the assessment of the air quality impacts of proposed developments and their significance.
- C.20 The impact of a development is usually assessed at specific receptors, and takes into account both the long-term background concentrations, in relation to the relevant Air Quality Assessment Level (AQAL) at these receptors, and the change with the development in place.
- C.21 The impact descriptors for individual receptors are detailed in Table C6.

Table C6: Impact Descriptors for Individual Receptors				
Long Term Average Concentration at Receptor in Assessment Year*	Percentage Change in Concentration Relative to Air Quality Assessment Level (AQAL)*			
	1%	2-5%	6-10%	>10
75% or less of AQAL	Negligible	Negligible	Slight	Moderate
76-94% of AQAL	Negligible	Slight	Moderate	Moderate
95-102% of AQAL	Slight	Moderate	Moderate	Substantial
103-109% of AQAL	Moderate	Moderate	Substantial	Substantial
110% or more of AQAL	Moderate	Substantial	Substantial	Substantial
*Percentage pollutant concentrations have been rounded to whole numbers, to make it easier to assess the impact. Changes of 0% (i.e. less than 0.5% or 0.2µg/m ³) should be described as Negligible				

Determining the Significance of Effects

- C.22 Impacts on air quality, whether adverse or beneficial, will have an effect on human health that can be judged as either 'significant' or 'not significant'.
- C.23 Once the impact of the proposed development has been assessed for the individual impacts, the overall significance is determined using professional judgement. This takes into account a number of factors such as:

¹⁴ Moorcroft and Barrowcliffe et al, Land-Use Planning and Development Control: Planning for Air Quality (v1.2), January 2017

- The existing and future air quality in the absence of the development;
- The extent of the current and future population exposure to the impacts; and
- The influence and validity of any assumptions adopted when undertaking the prediction of impacts.

Appendix D: Operational Phase Assessment Sensitivity Analysis

Existing Sensitive Receptors

- D.1 A sensitivity analysis has been undertaken, for NO₂ concentrations, in which Base Year background pollutant concentrations and vehicle emission factors have been used in the Opening/Future Year scenarios.
- D.2 Table D1 details the predicted NO₂ concentrations for the 2029 Opening/Future Year, for both the 'Without Development' and 'With Development' scenarios, for the sensitivity analysis. The impact has been assessed in accordance with the descriptors included in **Appendix C**.

Table D1: Predicted Unadjusted NO₂ Concentrations at Existing Sensitive Receptors for Scenarios 2 and 3 – Sensitivity Analysis

Receptor	Calculated Annual Mean NO ₂ Concentrations (µg/m ³) ^a				
	Without Development	With Development		Concentration Change as Percentage of AQAL	Impact ^b
		Concentration	Percentage in Relation to AQAL		
ESR 1	7.85	7.86	<75%	<0.5%	Negligible
ESR 2	7.64	7.65	<75%	<0.5%	Negligible
ESR 3	7.49	7.50	<75%	<0.5%	Negligible
ESR 4	7.34	7.40	<75%	<0.5%	Negligible
ESR 5	7.76	7.77	<75%	<0.5%	Negligible
ESR 6	7.66	7.68	<75%	<0.5%	Negligible
ESR 7	7.43	7.44	<75%	<0.5%	Negligible
ESR 8	7.68	7.68	<75%	<0.5%	Negligible
ESR 9	7.78	7.79	<75%	<0.5%	Negligible
ESR 10	8.21	8.24	<75%	<0.5%	Negligible
ESR 11	7.80	7.81	<75%	<0.5%	Negligible
ESR 12	7.42	7.43	<75%	<0.5%	Negligible
ESR 13	7.77	7.78	<75%	<0.5%	Negligible
ESR 14	7.78	7.79	<75%	<0.5%	Negligible
ESR 15	7.45	7.46	<75%	<0.5%	Negligible
ESR 16	7.37	7.38	<75%	<0.5%	Negligible

Table D1: Predicted Unadjusted NO₂ Concentrations at Existing Sensitive Receptors for Scenarios 2 and 3 – Sensitivity Analysis

Receptor	Calculated Annual Mean NO ₂ Concentrations (µg/m ³) ^a				
	Without Development	With Development		Concentration Change as Percentage of AQAL	Impact ^b
		Concentration	Percentage in Relation to AQAL		
ESR 17	7.24	7.24	<75%	<0.5%	Negligible
ESR 18	7.55	7.55	<75%	<0.5%	Negligible
ESR 19	8.43	8.45	<75%	<0.5%	Negligible
<i>a. NO₂ concentrations obtained by inputting predicted NO_x concentrations into the NO_x to NO₂ calculator, in accordance with LAQM.TG(22)</i> <i>b. Assessed using the Impact Descriptors from the EPUK/IAQM guidance, included in Appendix C. Changes of less than 0.5% should be described as negligible</i>					

Proposed Sensitive Receptors

- D.3 Pollutant concentrations have also been modelled for proposed receptors for the 2029 Opening/Future Year ‘With Development’ scenario, as part of the sensitivity analysis, as detailed in Table D2.

Table D2: Predicted Unadjusted NO₂ Concentrations at Proposed Sensitive Receptors for Scenario 3 – Sensitivity Analysis

Proposed Receptor	Calculated Annual Mean Concentrations (µg/m ³)	
	NO ₂	
PR 1	7.37	
PR 2	7.35	

Appendix E: Professional Experience of Assessors

- E.1 The assessment of air quality impacts, and the significance of the associated effects, takes into account the professional judgement of the assessor. Details of the experience of the personnel involved with the project are provided below:

Rachael Stiles

BSc (Hons), MSc, MIAQM, AMIEnvSc

Principal Environmental

Scientist (Air Quality)

Rachael is a Principal Air Quality Consultant at Wardell Armstrong. Rachael joined Wardell Armstrong in October 2021 but started her career as an air quality consultant in April 2018, after completing a BSc Physical Geography at Newcastle University and MSc in Sustainability (Environmental Consultancy and Project Management) at the University of Leeds.

Rachael has worked on a variety of infrastructure projects and has developed technical experience in air quality monitoring, detailed air quality assessments using dispersion modelling software such as ADMS roads, as well as construction dust assessments to support planning assessments (including extensive experience in Environmental Impact Assessments).

Malcolm Walton

BSc (Env Health) Dip (Acoustics & Noise Control)

MCIEH AMIOA

Technical Director

Malcolm holds a Bachelor of Science degree in Environmental Health and the Diploma in Acoustics and Noise Control. Malcolm is a Member of the Chartered Institute of Environmental Health and an Associate Member of the Institute of Acoustics. Malcolm joined Wardell Armstrong in September 2001 following 12 years working as an Environmental Health Officer in several local authorities, responsible for the enforcement of environmental legislation and in particular air pollution and noise nuisance.

Malcolm has experience in the technical co-ordination of environmental appraisal of large schemes to UK and international standards. Malcolm regularly carries out

and co-ordinates noise and air quality assessment work associated with planning applications including EIA work and PPC permit application/compliance. He regularly acts as expert witness in planning inquiries in respect of noise, air quality and odour.

DRAWINGS



KEY

Site Boundary

Existing Sensitive Receptors

Proposed Sensitive Receptors

Notes:

Boundaries are indicative. Aerial imagery shown for context purposes only.

REVISION	DETAILS	DATE	DRAWN	CHKD	APPD
CLIENT					
GLADMAN LTD					
PROJECT					
LAND OFF YORK CLOSE, MARKET BOSWORTH					
DRAWING TITLE					
EXISTING AND PROPOSED SENSITIVE RECEPTORS					
DRG No.		GM13363-002		REV	A
DRG SIZE		A3		SUIT. CODE	---
SCALE		1:10,000		DATE	04/07/2024
DRAWN BY		EK		APPROVED BY	MTW

STOKE-ON-TRENT

Sir Henry Doulton House
Forge Lane
Etruria
Stoke-on-Trent
ST1 5BD
Tel: +44 (0)1782 276 700

BIRMINGHAM

Two Devon Way
Longbridge Technology Park
Longbridge
Birmingham
B31 2TS
Tel: +44 (0)121 580 0909

BOLTON

41-50 Futura Park
Aspinall Way
Middlebrook
Bolton
BL6 6SU
Tel: +44 (0)1204 227 227

BRISTOL

Temple Studios
Temple Gate
Redcliffe
Bristol
BS1 6QA
Tel: +44 (0)117 203 4477

BURY ST EDMUNDS

Armstrong House
Lamdin Road
Bury St Edmunds
Suffolk
IP32 6NU
Tel: +44 (0)1284 765 210

CARDIFF

Tudor House
16 Cathedral Road
Cardiff
CF11 9LJ
Tel: +44 (0)292 072 9191

CARLISLE

Marconi Road
Burgh Road Industrial Estate
Carlisle
Cumbria
CA2 7NA
Tel: +44 (0)1228 550 575

EDINBURGH

Great Michael House
14 Links Place
Edinburgh
EH6 7EZ
Tel: +44 (0)131 555 3311

GLASGOW

24 St Vincent Place
Glasgow
G1 2EU
Tel: +44 (0)141 428 4499

LEEDS

36 Park Row
Leeds
LS1 5JL
Tel: +44 (0)113 831 5533

LONDON

Third Floor
46 Chancery Lane
London
WC2A 1JE
Tel: +44 (0)207 242 3243

NEWCASTLE UPON TYNE

City Quadrant
11 Waterloo Square
Newcastle upon Tyne
NE1 4DP
Tel: +44 (0)191 232 0943

TRURO

Baldhu House
Wheal Jane Earth Science Park
Baldhu
Truro
TR3 6EH
Tel: +44 (0)187 256 0738

International office:

ALMATY

29/6 Satpaev Avenue
Hyatt Regency Hotel
Office Tower
Almaty
Kazakhstan
050040
Tel: +7(727) 334 1310