

[illegible]

INSET DETAIL 1: SHRUB BED WITH Chunky Chip Longevity available from Suffolk Woodships Ltd BIODEGRADABLE "ECOTEX" - ECOTEX IS A BIODEGRADABLE SHEET MULCH - THIS IS AN IMPORTANT DESIGN CRITERION). NOT TO SCALE

NOTES

- Existing topsoil to be rotated to a depth of 400mm ensuring that the ground is completely broken up and in free draining. Complete ground preparation as specified within the measured works schedule. Existing finished soil levels are 50mm below adjacent pavement or grass surfaces. If soil is dry, water liberally, prior to laying sheet mulch.
- Suitable biodegradable sheet mulch such as Hyflex "Ecotex Multirun" to be unrolled and placed in overlapping rows (length to be a minimum of 50mm). To be laid by joining 200mm flap of material at the extreme edges of the shrub area, and folding over itself (refer to inset on sheet mulch specification). Tuck in sheet on the opposite side of the proposed shrub area and fasten close to tucked in part with plastic pegs.
- Suitable pegs hammered in at 500mm centres to secure sheeting. Increase frequency to 300mm centres at edges to secure sheet mulch at margins.
- Supply and pit plant shrubs through sheeting. Refer to pit planting through sheet mulch specification.
- Coarse graded free-of-fines large wood chip mulch to be darkened from aging (24 months minimum) such as Chunky Chip Longevity available from Suffolk Woodships Ltd. Mulch to cover all of biodegradable fabric to a min depth of 50mm over all plants are planted. Ensure finished levels are 15mm below adjacent turf or hard surfaces.

N.B. 6) Do not use biodegradable sheet mulch on slopes greater than 1:3 without the use of gravel boards at 1 - 1.5m centres along the contours to retain the bark cover.

7) For large triangle areas utilize a non-biodegradable polypropylene woven fabric such as "Concretex" from Hyflex UK Ltd, Ltd (07233) 220937. Cover the fabric all over with 40mm of clean, washed, cream / buff coloured gravel, 20mm gravel, unless otherwise stated in the key.

GENERAL NOTES:










- ALL DIMENSIONS IN MILLIMETRES
- DONOT SCALE OFF THIS DRAWING.
- (C) JAMES BLAKE ASSOCIATES 2024

PIT PLANTING THROUGH SHEET MULCH SPECIFICATION

- Place plants on sheet in intended positions
- Cut "X" shape in to the fabric with scissors or sharp knife for each plant position. Each cut to be approximately 200mm - 500mm depending on the size of the shrub.
- Press back the fabric using stones etc and excavate pits of appropriate size, for example -
 •500mm depth and 300mm radius of stem, for plants specified in 10L containers.
 •300mm depth and 200mm radius of stem, for plants specified in 3L or smaller containers.
- Ensure pit sides / base are well broken up.
- Pit plant in the nursery mark in line with the ground.
- Backfill with imported or existing topsoil mixed with Vitax "Q4 HN" fertiliser to suppliers instructions and 25L per plant compost per m².
- Firm in and replace 100g of fabric tightly around base of plant stem, ensure there is no soil what so ever over the sheet mulch. Peg as necessary.
- Water plants with 20L/plant for 10L stock and 10L/plant for 3L or smaller stock using a fine spray hose.
- Spread 100mm graded free-of-fines large wood chip mulch 50mm deep. Finished surface levels to be 15mm below adjacent turf or paving.

KEY

N

	PROPOSED FEATHERED TREE, INCLUDING STAKE AND TIE. SEE SPECIFICATION NOTES 1.1, 2.2, 2.3, 2.5, 3.1-3.4, 4.1-4.2 AND 5.1.
	PROPOSED STANDARD TREE, INCLUDING DOUBLE STAKE AND TIE. SEE SPECIFICATION NOTES 1.1, 2.2, 2.3, 2.5, 3.1-3.4, 4.1-4.2 AND 5.1.
	PROPOSED HEAVY STANDARD TREE, INCLUDING DOUBLE STAKE AND TIE. SEE SPECIFICATION NOTES 1.1, 2.2, 2.3, 2.5, 3.1-3.4, 4.1-4.2 AND 5.1. TREES WITHIN PROXIMITY TO HIGHWAYS TO HAVE 2M CLEAR STEM.
	PROPOSED EXTRA HEAVY STANDARD TREE, INCLUDING DOUBLE STAKE AND TIE. SEE SPECIFICATION NOTES 1.1, 2.2, 2.3, 2.5, 3.1-3.4, 4.1-4.2 AND 5.1. TREES WITHIN PROXIMITY TO HIGHWAYS TO HAVE 2M CLEAR STEM.
	PROPOSED CONIFEROUS OR BROAD LEAF EVERGREEN TREE, INCLUDING STAKE AND TIE. SEE SPECIFICATION NOTES 1.1, 2.2, 2.3, 2.5, 3.1-3.4, 4.1-4.2 AND 5.1.
	PROPOSED MULTISTEM TREE, INCLUDING UNDERGROUND GUYING. SEE SPECIFICATION NOTES 1.1, 2.2, 2.3, 2.5, 3.1-3.4, 4.1-4.2 AND 5.1.
	SHRUB AND HERBACEOUS PLANTING, INCLUDING BIODERGRADABLE SHEET AND BARK MULCH (ACCORDING TO SPECIFICATION). SEE SPECIFICATION NOTES 1.1-1.2, 2.1-2.3, 3.1-3.3, 4.1-4.2 AND 5.1.
	GROUND COVER PLANTING IN MIXES, INCLUDING BIODERGRADABLE SHEET AND BARK MULCH (ACCORDING TO SPECIFICATION). SEE SPECIFICATION NOTES 1.1-1.2, 2.1-2.3, 3.1-3.3, 4.1-4.2 AND 5.1.
	NATIVE WHIP AND SHRUB PLANTING IN MIXES, INCLUDING BIODERGRADABLE SHEET AND BARK MULCH (ACCORDING TO SPECIFICATION). SEE SPECIFICATION NOTES 1.1-1.2, 2.1-2.3, 3.1-3.3, 4.1-4.2 AND 5.1.
	HEDGE PLANTING, INCLUDING BIODERGRADABLE SHEET AND BARK MULCH (ACCORDING TO SPECIFICATION). REFER TO HEDGE SCHEDULES ON PLAN AND THE SCHEDULE OF QUANTITIES. SEE SPECIFICATION NOTES 1.1-1.2, 2.1-2.3, 3.1-3.3, 4.1-4.2 AND 5.1.
	HEDGE PLANTING, INCLUDING BIODERGRADABLE SHEET AND BARK MULCH (ACCORDING TO SPECIFICATION). INCLUDING TRIM BOARD EDGING TO SEPARATE FROM GRAVEL AREA. REFER TO HEDGE SCHEDULES ON PLAN AND THE SCHEDULE OF QUANTITIES. SEE SPECIFICATION NOTES 1.1-1.2, 2.1-2.3, 3.1-3.3, 4.1-4.2 AND 5.1.
	WASHED AND SCREENED, BUFF COLOURED GRAVEL, 20mm GAUGE, 40mm DEPTH, FINISHED LEVEL, 15mm BELOW ADJACENT SURFACES, LAID OVER "COVERTEXT" OVER LIGHTLY CONSOLIDATED SUBGRADE.
	SEEDED GRASS AREA. REFER TO PLANT SCHEDULE FOR SPECIFICATION OF MIX.
	CULTIVATED TURF UNLESS OTHERWISE STATED ON PLAN. SEE SPECIFICATION NOTES B4, C5 AND E1.
	WILDFLOWER SEEDED AREA. REFER TO PLANT SCHEDULE FOR SPECIFICATION OF MIX.
	WET WILDFLOWER SEEDED AREA. REFER TO PLANT SCHEDULE FOR SPECIFICATION OF MIX.
	MARGINAL PLANT PLANTED AREA. REFER TO PLANT SCHEDULE FOR SPECIFICATION OF MIX.
	BULB PLANTING IN MIXES, SPRING FLOWERING VARIETIES. REFERS TO SCHEDULE FOR FURTHER INFORMATION.
	CLIMBING SHRUB IN SHRUB BEDS, GRASS/ GRAVEL OR IN PITS IN PAVING (SEE PLAN), TWINNING VARIETIES (MARKED) ? SEE NOTE C7. SELF CLIMBING VARIETIES (MARKERS) ? SEE NOTE G6. SEE SPECIFICATION NOTES C1-3, C8, D1-2 AND E1.
	SPECIMEN SHRUBS IN SHRUB BEDS OR PIT PLANTED IN GRASS/GRASS/GRASS. SPECIMEN SHRUBS IN GRASS ARE MEASURED SEPARATELY IN SCHEDULE OF QUANTITIES. SEE SPECIFICATION NOTES A1, B1-3, C1-3, D1-2 AND E1.
	EXISTING TREE TO BE RETAINED. SEE GENERAL NOTE A1 AND E1. IF PREPARED, SEE ALSO JAMES BLAKE ASSOCIATES PLAN AND SCHEDULE FOR ANY SURGERY WORKS.
	EXISTING VEGETATION GROUND OR HEDGE TO BE RETAINED. SEE GENERAL NOTE A1 AND E1. IF PREPARED, SEE ALSO JAMES BLAKE ASSOCIATES PLAN AND SCHEDULE FOR ANY SURGERY WORKS.
	EXISTING GROUND/FLORA TO BE RETAINED AND ENHANCED THROUGH OVERSEEDING.
	SPIRAL BENCH, AVAILABLE FROM MIRACLE DESIGN AND PLAY, TEL: 01604 656240 OR SIMILAR AND APPROVED.
	BBQ, AVAILABLE FROM MIRACLE DESIGN AND PLAY, TEL 01604 656240 OR SIMILAR AND APPROVED.
	PLAY EQUIPMENT AVAILABLE FROM MIRACLE DESIGN AND PLAY, TEL: 01604 656240 OR SIMILAR AND APPROVED.
	WET POUT SAFETY SURFACING BY MIRACLE PLAY AND DESIGN, TEL: 01604 656240, OR SIMILAR AND APPROVED.
	PLAY MOUNDS AND BOULDERS
	MOWN LAWN FOOTPATHS. REFER TO PLANT SCHEDULE FOR SPECIFICATION OF MIX.
	ROOT BARRIER, RE-ROOT 1000, AVAILABLE FROM GREEN BLUE URBAN.
	HOGGIN PLANT WITH PRESSURE TREATED TIMBER EDGE, OVER COMPACTED MOT & SUBGRADE, OVER TERRAM 1000 GEOTEXTILE OR SIMILAR APPROVED.
	KNEE RAIL, 450mm HIGH, COMPRISING 125 x 125mm SAWN SOUTHWOOD WEATHERED TWICE POSTS TO BE LOCATED BEHIND THE RUN OF KNEE RAIL, TO ENSURE THE ACCESS POINT POLE CAN BE PULLED OUT. POLE TO BE 4m LONG TO COVER THE 3.6m ABOVE ACCESS POINT WITH WELDED STEEL STOP PLATE 100x100mm. TO BE DRILLED WITH 50mm DIA. TO BE DRILLED WITH 8mm HOLE VERTICALLY WITH IN 20mm OF END TO RECEIVE HEAVY DUTY PALOOCK, 800mm ABOVE GROUND AND 800 BELOW (1600mm TOTAL) DRILLED WITH 50MM TO RECEIVE HOT DIPPED GALVANIZED MILD STEEL TUBE 48mm DIAMETER. POLES TO BE JOINED WITH MALE AND FEMALE SCREW FIT PARTS JOINS TO OCCUR WITHIN POSTS. HEIGHTS TO BE INCREASED.
	3 BAR POST AND RAIL FENCING, 1.2m HIGH WITH MAINTENANCE GATE TO MATCH.

NO.	DATE	BY/ISS	STATUS	REVISIONS
1	20/06/2024	JA	ISSUED	REVISIONS TO BE MADE TO THE PROPOSAL FOR THE 20/06/2024 DATE. THE PROPOSAL IS TO BE SUBMITTED TO THE CLIENT FOR APPROVAL. THE PROPOSAL IS TO BE SUBMITTED TO THE CLIENT FOR APPROVAL. THE PROPOSAL IS TO BE SUBMITTED TO THE CLIENT FOR APPROVAL.
2	20/06/2024	JA	ISSUED	REVISIONS TO BE MADE TO THE PROPOSAL FOR THE 20/06/2024 DATE. THE PROPOSAL IS TO BE SUBMITTED TO THE CLIENT FOR APPROVAL. THE PROPOSAL IS TO BE SUBMITTED TO THE CLIENT FOR APPROVAL.